


2022



Commel®




Commel[®]

Kabelske motalice - heavy duty line / Cable Reels - Heavy Duty Line	8
Kabelske motalice - profi line / Cable Reels - Profi Line	14
Kabelske motalice - hobby line / Cable Reels - Hobby Line	22
Razdjelni ormari / Mobile Power Stations	28
Priključni kabeli / Connection Cables	30
Produžni kabeli - profi line / Extension Cables - Profi Line	34
Produžni kabeli - hobby line / Extension Cables - Hobby Line	42
Prenaponska zaštita / Surge Protection	46
Prenosive utičnice / Extension Sockets	48
Industrijski utikači, natikači i utičnice / CEE Plugs, Connectors and Sockets	52
Utikači, natikači i utičnice / Plugs, Connectors and Sockets	58
Razdjelnici, adapteri i blokade / Adaptors and Direct contact protection	64
Kućna automatizacija / Home Automation	68
Multimetri i ispitivači napona / Multimeters and Voltage Testers	76
Zvonca / Doorbells	80
Portafoni / Door Phones	84
Ventilatori / Exhaust Fans	88
Automatski osigurači i FID sklopke / RCD Switch and Miniature Circuit Breaker	90
Montažni pribor / Mounting Accessories	92
Spojni pribor / Connection Accessories	98
Izolacijski pribor / Insulation Accessories	106

Tuljci i stopice / Wire Terminals	110
Električarski alati / Hand Tools	114
LED žarulje / LED Bulbs	118
LED Trake / LED Strip Lights	124
Zidne i stropne LED svjetiljke / LED Under Cabinet Light Fixtures	126
Zidne i stropne svjetiljke / Bulkhead Light Fixtures	130
LED plafonjere / LED Ceiling Lamps	132
LED paneli / LED Panels	136
LED ugradbene svjetiljke / LED Downlights	144
LED cijevi / LED Tubes	146
LED vodotijesne svjetiljke / LED Waterproof Light Fixtures	148
Panik svjetiljke / Emergency Light Fixtures	152
Solarni LED reflektori / Solar LED Floodlights	154
LED reflektori / LED Floodlights	156
Akumulatorski LED reflektori / Rechargeable LED Floodlights	162
Radne i prenosive svjetiljke / Inspection and Portable Lamps	164
Noćno svjetlo / Night Light	168
Detektori pokreta i luksomati / Motion Detectors and Photocell Sensors	170
Grla i pribor za rasvjetu / Bulb Sockets and Lighting Accessories	174
Izlaganje asortimana / Point of Sale Display Units	178

OZNAKE I NAMJENA KABELA U KATALOGU CODES AND USAGE GUIDE FOR CABLES IN THE CATALOGUE



H07RN-F



Namjena:
 Za trajnu vanjsku upotrebu u vlažnim i suhim uvjetima, pri temperaturama od -25°C do +60°C.

Karakteristike:
 Visoka fleksibilnost i otpornost na ulja, kiseline, vremenske prilike, niske temperature i velika mehanička opterećenja.

Use:
 For long-term outdoor use in wet and dry conditions, at temperatures from -25° C to +60° C.

Characteristics:
 High flexibility and resistance to oils, acids, weather conditions, low temperatures and high mechanical stress.

AT N07V3V3-F



Namjena:
 Za trajnu vanjsku upotrebu u vlažnim i suhim uvjetima, pri temperaturama od -35°C do +70°C.

Karakteristike:
 Otpornost na ulja, velika mehanička opterećenja i niske temperature. Visoka fleksibilnost pri temperaturama do čak -35°C.

Use:
 For long-term outdoor use in wet and dry conditions, at temperatures from -35° C to +70° C.

Characteristics:
 Resistance to oils, high mechanical stress and low temperatures. High flexibility even at temperatures as low as -35°C.

H05RR-F



Namjena:
 Za privremenu vanjsku upotrebu, pri temperaturama od -25 °C do +60 °C.

Karakteristike:
 Visoka fleksibilnost i otpornost na manja mehanička opterećenja.

Use:
 For short-term outdoor use at temperatures from -25 ° C to +60 ° C.

Characteristics:
 High flexibility and resistance to low mechanical stress.

H05VV-F



Namjena:
 Za svakodnevnu upotrebu u suhim uvjetima, pri temperaturama od +5 °C do +70 °C.

Karakteristike:
 Visoka fleksibilnost i otpornost na manja mehanička opterećenja.

Use:
 For everyday use in dry conditions, at temperatures from +5 °C do +70 °C.

Characteristics:
 High flexibility and resistance to low mechanical stress.

DOŽIVOTNO JAMSTVO

Commel kabelske motalice se već dugu niz godina ističu svojom **kvalitetom** i pouzdanošću. Zahvaljujući širokom asortimanu, svaki će korisnik u našoj ponudi pronaći **idealnu** kabelsku motalicu za svoje potrebe. Proizvodi iz ove kategorije opremljeni su **vrhunskim** komponentama, ručno su sastavljeni i pažljivo prekontrolirani prije isporuke. Svaki pojedini artikl prolazi završno ispitivanje po sistemu dvostruke kontrole, te je označen serijskim brojem radi osiguravanja sljedivosti. Kao dodatnu **sigurnost**, od sada svim kupcima Commel kabelskih motalica dajemo DOŽIVOTNO JAMSTVO. Kupnjom Commel kabelske motalice dobivate vrhunski proizvod europske kvalitete koji ćete koristiti **doživotno**.

Što je pokriveno Commel doživotnim jamstvom?

Commel doživotno jamstvo pokriva sve tvorničke greške, nedostatke u materijalu ili nedostatke u izradi koji mogu utjecati na funkciju proizvoda, a koji su uočeni pri normalnoj upotrebi i poštivanju svih tehničkih specifikacija proizvoda.

Koliko traje jamstvo?

Doživotno! Ovdje nema trikova ni sitnih slova. Doživotno jamstvo doslovno i znači doživotno jamstvo! Jamstvo vrijedi do kraja životnog vijeka svake osobe koja kupi kabelsku motalicu Commel sa oznakom doživotnog jamstva i registrira se na našim web stranicama.

Kako aktivirati jamstvo?

Za aktivaciju doživotnog jamstva potrebno je registrirati proizvod u roku trideset (30) dana od dana kupnje. Obrazac za registraciju proizvoda nalazi se na linku: <http://www.commel.hr/aktivacija-jamstva/>. Nakon registracije ćete dobiti Vaš osobni certifikat doživotnog jamstva.

Tko može koristiti doživotno jamstvo?

Commel doživotno jamstvo može koristiti isključivo originalni kupac proizvoda. Jamstvo nije prenosivo na druge osobe.

LIFETIME WARRANTY

Commel cable reels have been well known for their quality and **safety** for many years. Thanks to a wide assortment, every user can find the **ideal** cable reel for their needs. The products from this category are equipped with **top quality** components, hand-assembled and carefully checked before delivery. During the production, each item passes through the double checking system before the final **quality** control check and is marked with a serial number to ensure the traceability. To prove our confidence in their quality and safety, we now **provide** LIFETIME WARRANTY to all buyers of Commel cable reels. Purchasing the Commel cable reels, you get a top quality European product you will use for a **lifetime**.

What is covered under the Commel Lifetime Warranty?

Commel Lifetime Warranty covers all manufacturing defects, as well as defects in materials and workmanship that may affect the function of the product, which are noticed when used in normal conditions and in accordance with all technical specifications of the product.

How long the warranty lasts?

A lifetime! There are no tricks or small print here. Lifetime Warranty literally means lifetime warranty! It means that it covers a lifetime of any person who buys the Commel cable reel with a Lifetime Warranty mark and is registered on our web site.

How to activate the Lifetime Warranty?

To activate the Lifetime Warranty, you must register the product within thirty (30) days from the date of purchase. The product registration form is available on the following link: <http://www.commel.hr/en/warranty-activation/>. After the registration you will receive your personal Lifetime Warranty Certificate.

Who can use this Lifetime Warranty?

Commel Lifetime Warranty can only be used by the original buyer of the product. The warranty is not transferable to other persons.



Kabelske motalice

Ugradnjom vrhunskih komponenti i korištenjem najotpornijih kabela stvorili smo liniju proizvoda namijenjenu profesionalnim korisnicima u najzahtjevnijim uvjetima rada. Heavy duty line kabelske motalice odlikuju otpornost na sve vremenske uvjete, vlagu, visoke i niske temperature i velika mehanička opterećenja.



Cable Reels

With top quality components and the most resistant cables, we have created a product line for professional use in the most demanding conditions. Heavy Duty Line cable reels are resistant to all weather conditions, humidity, high and low temperatures and high mechanical stress.

- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Kočnica koja sprječava nekontrolirano odmatanje kabela
Brake mechanism that prevents the cable from accidental unwinding
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch




Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	AVAILABLE STANDARDS			Utičnik / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/cin	EAN
					SCHUKO / TYPE F	FRENCH / TYPE E	BRITISH / TYPE G					
200-390	H07RN-F 5G2,5	25 m	crna / black	1 x CEE 400 V~ / 16 A 2 x 230 V~ / 16 A				CEE 400 V~ / 16 A	280 mm	IP44	1	3858890447644
200-391	AT N07V3V3-F 5G2,5	25 m	žuta / yellow	1 x CEE 400 V~ / 16 A 2 x 230 V~ / 16 A				CEE 400 V~ / 16 A	280 mm	IP44	1	3858890444506
200-392	H07RN-F 5G1,5	40 m	crna / black	1 x CEE 400 V~ / 16 A 2 x 230 V~ / 16 A				CEE 400 V~ / 16 A	280 mm	IP44	1	3858890447651



- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Kočnica koja sprječava nekontrolirano odmatanje kabela
Brake mechanism that prevents the cable from accidental unwinding
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-393	H07RN-F 5G2,5	25 m	crna / black	1 x 400 V~ / 16 A 2 x 230 V~ / 16 A	400 V~ / 16 A	280 mm	IP44	1	3858890447668
200-394	AT N07V3V3-F 5G2,5	25 m	žuta / yellow	1 x 400 V~ / 16 A 2 x 230 V~ / 16 A	400 V~ / 16 A	280 mm	IP44	1	3858890447675
0934	H05RR-F 5G2,5	25 m	crna / black	1 x 400 V~ / 16 A 2 x 230 V~ / 16 A	400 V~ / 16 A	280 mm	IP44	1	3859888761971



- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch
- Rotirajuća ergonomska ručica
Rotating ergonomic handle




Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-381	H07RN-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447590
200-382	AT N07V3V3-F 3G1,5	50 m	žuta / yellow	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447606



- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch
- Rotirajuća ergonomska ručica
Rotating ergonomic handle
- Svjetlosni indikator napona
Power indicator light

MADE IN EUROPE



MADE IN EUROPE

- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch
- Rotirajuća ergonomska ručica
Rotating ergonomic handle
- Svjetlosni indikator napona
Power indicator light
- Metalni bubanj
Metal reel

AVAILABLE STANDARDS



Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0983	H07RN-F 3G2,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858883831542
200-363	AT N07V3V3-F 3G2,5	40 m	žuta / yellow	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890444513
200-364	H07RN-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447705
200-365	AT N07V3V3-F 3G1,5	50 m	žuta / yellow	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447712
200-366	H07RN-F 3G1,5	30 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447729
200-367	AT N07V3V3-F 3G1,5	30 m	žuta / yellow	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3858890447736

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-321	H07RN-F 3G2,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401234
200-322	H07RN-F 3G1,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401241
200-323	AT N07V3V3 3G2,5	40 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401258
200-324	AT N07V3V3 3G1,5	50 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401265




Kabelske motalice

...za beskompromisne korisnike koji traže samo vrhunsku kvalitetu i neupitnu pouzdanost u svim uvjetima rada. Robusnost kućišta, bubnja, utičnica, kabela i ostalih komponenti je ono što ove motalice čini posebnima. Često se susrećemo sa Commel profi kabelskim motalicama koje se koriste i više od 20 godina. Napravljeno da traje!

Cable Reels

...for uncompromising users seeking only top quality and unmatched reliability under all operating conditions. The robustness of the housing, drum, sockets, cable, and other components is what makes these reels special. You can often come across Commel Profi Line cable reels that have been used for more than 20 years. Made to last!



MADE IN EUROPE

- Utičnice s poklopcem omogućavaju stupanj zaštite IP44
Sockets with lid provide IP44 degree of protection
- Rotirajuća ergonomska ručica
Rotating ergonomic handle
- Ugrađena zaštita od preopterećenja – termoprekidač
Built-in overload protection – thermo switch
- Svjetlosni indikator napona
Power indicator light

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0912	H05VV-F 3G2,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3859888558779
0932	H05RR-F 3G2,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	300 mm	IP44	1	3859888558854



MADE IN EUROPE



Utičnice s poklopcem omogućavaju stupanj zaštite IP44

Sockets with lid provide IP44 degree of protection

Ugrađena zaštita od preopterećenja – termoprekidač

Built-in overload protection – thermo switch

Svjetlosni indikator napona

Power indicator light

AVAILABLE STANDARDS	SCHUKO / TYPE F	FRENCH / TYPE E	BRITISH / TYPE G
---------------------	-----------------	-----------------	------------------

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-360	H07RN-F 3G2,5	40 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447743
0982	H05RR-F 3G2,5	40 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3859889306973
0980	H05RR-F 3G2,5	25 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3859889306966
200-368	H05RR-F 3G1,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447750
200-369	H05RR-F 3G1,5	25 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447767
200-371	AT N07V3V3-F 3G2,5	25 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024403474
200-362	AT N07V3V3-F 3G1,5	40 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890444520
200-361	AT N07V3V3-F 3G1,5	25 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890444537
200-370	H05RR-F 3G1,5	15 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP44	1	3858890447774



MADE IN EUROPE

Utičnice s poklopcem omogućavaju stupanj zaštite IP44

Sockets with lid provide IP44 degree of protection

Ugrađena zaštita od preopterećenja – termoprekidač

Built-in overload protection – thermo switch

Svjetlosni indikator napona

Power indicator light

Rotirajuća ergonomska ručica

Rotating ergonomic handle

Metalni bubanj

Metal reel

AVAILABLE STANDARDS	SCHUKO / TYPE F	FRENCH / TYPE E	BRITISH / TYPE G
---------------------	-----------------	-----------------	------------------

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-340	H07RN-F 3G2,5	40 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447781
0930	H05RR-F 3G2,5	40 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3859889306959
0928	H05RR-F 3G2,5	25 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3859889306942
200-341	H05RR-F 3G1,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447798
200-342	H05RR-F 3G1,5	25 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447804
200-372	AT N07V3V3-F 3G2,5	25 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024403481
200-343	AT N07V3V3-F 3G1,5	40 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447811
200-344	AT N07V3V3-F 3G1,5	25 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447828



MADE IN EUROPE




- Utičnice s poklopcem omogućavaju stupanj zaštite IP44**
 Sockets with lid provide IP44 degree of protection
- Ugrađena zaštita od preopterećenja – termoprekidač**
 Built-in overload protection – thermo switch
- Svjetlosni indikator napona**
 Power indicator light
- Metalni bubanj**
 Metal reel
- Rotirajuća ergonomska ručica**
 Rotating ergonomic handle



Konstrukcija prilagođena za izvođenje profesionalnih radova, kao i za hobi korisnike. Utičnice se nalaze na kraju kabela, stoga nema potrebe za premještanjem motalice za vrijeme obavljanja radova.

Construction designed for professional as well as for hobby users. Sockets are at the end of the cable, so there is no need to move around the cable reel during the work.

MADE IN EUROPE



- Ugrađena zaštita od preopterećenja – termoprekidač**
 Built-in overload protection – thermo switch
- Svjetlosni indikator napona**
 Power indicator light
- Gumirani trostruki razdjelnik otporan na udarce**
 Shock resistant rubber 3-way socket outlet

AVAILABLE STANDARDS			
	SCHUKO / TYPE F	FRENCH / TYPE E	BRITISH / TYPE G


Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-325	H05RR-F 3G2,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401272
200-326	H05RR-F 3G1,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3856024401289

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-313	H07RN-F 3G1,5	40 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447835
0945	H05RR-F 3G1,5	50 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858883834222
0944	H05RR-F 3G1,5	25 m	crna / black	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858883834260
200-312	AT N07V3V3-F 3G1,5	40 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890444544
200-311	AT N07V3V3-F 3G1,5	25 m	žuta / yellow	3 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890444551




Konstrukcija motalice je prilagođena za upotrebu s vrtnim električnim alatima. Utičnica se nalazi na kraju kabela, stoga nema potrebe za premještanjem motalice za vrijeme obavljanja radova.

The construction of the reel is designed for use with garden power tools. The socket is at the end of the cable so there is no need to move around the cable reel during the work.



- Ugrađena zaštita od preopterećenja - termoprekidač**
Built-in overload protection – thermo switch
- Svjetlosni indikator napona**
Power indicator light
- PVC ručtica**
PVC handle



Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
200-351	AT N07V3V3-F 3G1,5	25 m	žuta / yellow	1 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447842
200-352	AT N07V3V3-F 3G1,5	40 m	žuta / yellow	1 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP44	1	3858890447859



Commel MARINKO grupa proizvoda je opremljena specijalnim MarinFlex kablom otpornim na abrazivna djelovanja morske vode. MarinFlex kabl moguće je koristiti u uvjetima trajnog ili povremenog kontakta s morskom vodom, a odlikuju ga izvrsna fleksibilnost i otpornost na visoke i niske temperature. Posebno je pogodan za električni priključak plovila u marinama jer je jednostavan za održavanje, lako se čisti i ne ostavlja tragove na površinama.

The Commel MARINKO product group is equipped with a special MarinFlex cable resistant to the abrasive action of sea water. The MarinFlex cable can be used in conditions of permanent or occasional contact with sea water, and it has excellent flexibility and resistance to high and low temperatures. It is especially suitable for the electrical connection of boats in the marinas because it is easy to maintain, easy to clean and leaves no traces on the surfaces.



Upotreba u marinama
Suitable for use in Marinas



Upotreba u ribogojilištima
Suitable for use in Fish Farms



Upotreba za električni priključak plovila
Boat electrical connection



- Utičnice s poklopcem omogućavaju stupanj zaštite IP44**
Sockets with lid provide IP44 degree of protection
- Ugrađena zaštita od preopterećenja - termoprekidač**
Built-in overload protection – thermo switch
- Kočnica koja sprječava nekontrolirano odmatanje kabela**
Brake mechanism that prevents the cable from accidental unwinding

- Ugrađena zaštita od preopterećenja - termoprekidač**
Built-in overload protection – thermo switch
- Svjetlosni indikator napona**
Power indicator light
- PVC ručtica**
PVC handle

Slika / Photo	Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
1	200-398	MarinFlex 3G1,5	25 m	narandžasta / orange	1 x CEE 230 V~ / 16 A 2 x 230 V~ / 16 A	CEE 230 V~ / 16 A	280 mm	IP44	1	3858890449693
2	200-397	MarinFlex 3G1,5	25 m	narandžasta / orange	CEE 230 V~ / 16 A	CEE 230 V~ / 16 A	280 mm	IP44	1	3858890449686

HOBBY LINE

Kabelske motalice

Sam naziv linije sugerira da se radi o proizvodima namijenjenim manje zahtjevnim korisnicima. No, modele iz ove kategorije često ćete naći i u rukama pravih profesionalaca. Visoka kvaliteta ugrađenih komponenti osigurava vrlo dugi radni vijek proizvoda. Pocinčani nosač, ugrađeni termoprekidač, utičnice sa zaštitom za djecu, metalni ili PVC bubanj pojačane otpornosti na lomove, samo su neki od detalja koji čine proizvode iz ove kategorije idealnim za svakog korisnika.

Cable Reels

The name of the line itself suggests that these products are made for less demanding users. However, some of the products from this line can often be seen used by professional workers. The high quality of the built-in components guarantees a very long lifespan. Galvanized frame, built-in thermo switch, sockets with Direct contact protection, metal or PVC reel with enhanced resistance to fracture, these are just some of the features that make the products in this category ideal for every user.



- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection - thermo switch
- Rotirajuća ergonomska ručica
Rotating ergonomic handle
- Svjetlosni indikator napona
Power indicator light
- Metalni bubanj
Metal reel
- PVC ručica
PVC handle

AVAILABLE STANDARDS



Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičnik / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0931	H05RR-F 3G2,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558847
0929	H05RR-F 3G2,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558830
0927	H05RR-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558823
0925	H05RR-F 3G1,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558816
0911	H05VV-F 3G2,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558762
0909	H05VV-F 3G2,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558755
0907	H05VV-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558748
0905	H05VV-F 3G1,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558731



- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection – thermo switch
- Svjetlosni indikator napona
Power indicator light
- PVC ručkica
PVC handle

AVAILABLE STANDARDS	SCHUKO / TYPE F			FRENCH / TYPE E			BRITISH / TYPE G		
									

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičać / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0981	H05RR-F 3G2,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558984
0979	H05RR-F 3G2,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558977
0977	H05RR-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558960
0975	H05RR-F 3G1,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP20	1	3859888558953
0961	H05VV-F 3G2,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558946
0959	H05VV-F 3G2,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558939



- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection – thermo switch

AVAILABLE STANDARDS	SCHUKO / TYPE F			FRENCH / TYPE E			BRITISH / TYPE G		
									

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičać / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0957	H05VV-F 3G1,5	50 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859888558922
0956	H05VV-F 3G1,5	40 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3858883839173
0955	H05VV-F 3G1,5	25 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP20	1	3859888558915
0960	H05VV-F 3G1,5	20 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP20	1	3858883839210
0953C	H05VV-F 3G1,5	15 m	crna / black	4 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP20	1	3858883831573






Konstrukcija motalice je prilagođena za upotrebu s vrtnim električnim alatima. Utičnica se nalazi na kraju kabela, stoga nema potrebe za premještanjem motalice za vrijeme obavljanja radova. Crvena boja kabela se koristi radi lakše vidljivosti kako bi se izbjegla oštećenja pri slučajnom kontaktu s električnim alatom u radu.

The construction of the reel is designed for use with garden power tools. The socket is at the end of the cable so there is no need to move around the cable reel during the work. The red color of the cable is used for better visibility in order to avoid damage during accidental contact with the power tools at work.



- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection – thermo switch
- Svjetlosni indikator napona
Power indicator light

AVAILABLE STANDARDS	SCHUKO / TYPE F	FRENCH / TYPE E



Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0991	H05VV-F 3G1,5	25 m	crvena / red	1 x 230 V~ / 16 A	230 V~ / 16 A	230 mm	IP20	1	3859889306980
0993	H05VV-F 3G1,5	40 m	crvena / red	1 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3858890442755
0992	H05VV-F 3G1,5	50 m	crvena / red	1 x 230 V~ / 16 A	230 V~ / 16 A	280 mm	IP20	1	3859889306997

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Utičnice / Sockets	Utičak / Plug	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0890	H05VV-F 3G1	10 m	bijela / white	4 x 230 V~ / 10 A	230 V~ / 16 A	IP20	1	3859889306812

- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection – thermo switch



PRAZNE KABELSKE MOTALICE
EMPTY CABLE REELS

- Ugrađena zaštita od preopterećenja - termoprekidač
Built-in overload protection – thermo switch

Šifra / Art. No.	Utičnice / Sockets	Promjer motalice / Reel diameter	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0998	4 x 230 V~ / 16 A	230 mm	IP20	1	3859888761773
0999	4 x 230 V~ / 16 A	280 mm	IP20	1	3859888761834





Razdjelni ormari

Commel asortiman razdjelnih ormara je potpuno prilagođen za industrijske, građevinske i ostale profi radove i jamči pouzdano i sigurno korištenje električne energije kod teških uvjeta rada.

Mobile Power Stations

Commel's range of mobile power stations is fully adapted for industrial, construction and other professional work and guarantees reliable and safe use of electricity when operating at heavy-duty conditions.

Commel®



Commel razdjelni ormari Vam omogućuju mobilan i praktičan priključak na električnu energiju u svim situacijama na gradilištima i u industriji. Robusna čelična konstrukcija plastificirana signalnom žutom bojom omogućava jednostavnost prijenosa i sigurnost pri postavljanju na mjesto rada. Fleksibilni gumeni kabel pruža sigurnost u radu i kod ekstremnih uvjeta (vlaga, ulja i mehanička opterećenja). Za zaštitu ljudi i opreme ugrađuju se grebenaste sklopke, instalacijski automatski osigurači i strujne zaštitne sklopke. Ugrađene komponente izrađene su prema zahtjevima međunarodnih normi.

Commel mobile power stations provide a mobile and convenient connection to electricity in all situations at construction sites and in industry. Robust steel construction plasticized with signal yellow color allows easy mobility and safety when set to work. Flexible rubber cable provides safety during work even under heavy-duty conditions such as humidity, oil and mechanical stress. CAM switches, circuit breakers and RCD switches are built in for the protection of people and equipment. Built-in components comply with the requirements of international standards.



MADE IN EUROPE



MOGUĆNOST IZBORA OPREME NA UPIT
OPTIONAL EQUIPMENT AVAILABLE ON REQUEST





Priključni kablei

Commel priključni kabeli namijenjeni su spajanju svih vrsta električnih aparata na električnu mrežu. Bilo da je riječ o njihovoj ugradnji odmah u tvornici na električni aparat ili da to sami radite kod kuće, bolji i pouzdaniji priključak Vašeg aparata na električnu mrežu niste mogli odabrati! Garancija vrhunske kvalitete je posjedovanje VDE certifikata.

Connection Cables

Commel connection cables are designed for connecting all types of electrical appliances to the power supply. Whether they are already installed in an electrical appliance by producer or you are doing that by yourself at home, you can be sure that you are using the most reliable connection of your appliance to the power supply! The top quality of Commel connection cables has been approved and confirmed by VDE Testing and Certification Institute.



PRIKLJUČNI KABLI S EURO UTIKAČEM
CONNECTION CABLES WITH EURO PLUG



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0114	H03VVH2-F 2x0,75	2 m	bijela / white	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558199
0115	H03VVH2-F 2x0,75	2 m	crna / black	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558205
272-175	H03VVH2-F 2x0,75	2 m	smeđa / brown	2,5 A / 250 V~	2,5 A	250 V~	20	3856024401968
272-176	H03VVH2-F 2x0,75	2 m	zlatna / gold	2,5 A / 250 V~	2,5 A	250 V~	20	3856024401975
0118	H03VVH2-F 2x0,75	3 m	bijela / white	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558212
0119	H03VVH2-F 2x0,75	3 m	crna / black	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558229

PRIKLJUČNI KABLI S EURO UTIKAČEM I SKLOPKOM
CONNECTION CABLES WITH EURO PLUG & SWITCH




Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0112	H03VVH2-F 2x0,75	2 m	bijela / white	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558427
0113	H03VVH2-F 2x0,75	2 m	crna / black	2,5 A / 250 V~	2,5 A	250 V~	20	3859888558434
0128	H03VVH2-F 2x0,75	2 m	zlatna / gold	2,5 A / 250 V~	2,5 A	250 V~	20	3859889306683
272-185	H03VVH2-F 2x0,75	2 m	smeđa / brown	2,5 A / 250 V~	2,5 A	250 V~	20	3856024401982
0116	H03VVH2-F 2x0,75	3 m	bijela / white	2,5 A / 250 V~	2,5 A	250 V~	20	3859889306287
0117	H03VVH2-F 2x0,75	3 m	crna / black	2,5 A / 250 V~	2,5 A	250 V~	20	3859889306300



Kabeli s tekstilnim plaštem najčešće se koriste za ugradnju u glačala i slične uređaje kod kojih postoji mogućnost kontakta kabela s vrućom površinom.

Cables with textile sheath are most commonly used on electric irons and certain other kinds of appliances which have a high risk of the cable being exposed to very high temperatures, by direct contact with the heating element.

MADE IN EUROPE




ŠUKO PRIKLJUČNI KABELO S TEKSTILNIM PLAŠTEM

SCHUKO CONNECTION CABLES WITH TEXTILE SHEATH

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0333	H03RT-H 3G0,75	2 m	bijela / white	16 A / 250 V~	6 A / 1300 W	250 V~	20	3859888558403
0339	H03RT-H 3G0,75	3 m	bijela / white	16 A / 250 V~	6 A / 1300 W	250 V~	20	3859888558410
272-401	H03RT-H 3G1	2 m	bijela / white	16 A / 250 V~	10 A / 2200 W	250 V~	20	3858890448504
272-402	H03RT-H 3G1	3 m	bijela / white	16 A / 250 V~	10 A / 2200 W	250 V~	20	3858890448511

MADE IN EUROPE



ŠUKO PRIKLJUČNI KABELO S PVC PLAŠTEM

SCHUKO CONNECTION CABLES WITH PVC SHEATH

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0310	H05VV-F 3G0,75	1,5 m	bijela / white	16 A / 250 V~	6 A / 1300 W	250 V~	20	3859888558601
0311	H05VV-F 3G0,75	1,5 m	crna / black	16 A / 250 V~	6 A / 1300 W	250 V~	20	38598889306508
0314	H05VV-F 3G0,75	2 m	bijela / white	16 A / 250 V~	6 A / 1300 W	250 V~	20	3859888558236
0315	H05VV-F 3G0,75	2 m	crna / black	16 A / 250 V~	6 A / 1300 W	250 V~	20	38598889306089
0318	H05VV-F 3G0,75	3 m	bijela / white	16 A / 250 V~	6 A / 1300 W	250 V~	20	3859888558243
0319	H05VV-F 3G0,75	3 m	crna / black	16 A / 250 V~	6 A / 1300 W	250 V~	20	38598889306102
0481	H05VV-F 3G1	1,5 m	bijela / white	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833249
0482	H05VV-F 3G1	1,5 m	crna / black	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833256
0484	H05VV-F 3G1	2 m	bijela / white	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833263
0486	H05VV-F 3G1	2 m	crna / black	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833270
0488	H05VV-F 3G1	3 m	bijela / white	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833287
0489	H05VV-F 3G1	3 m	crna / black	16 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833294
0512	H05VV-F 3G1,5	1,5 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558625
0511	H05VV-F 3G1,5	1,5 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558618
0514	H05VV-F 3G1,5	2 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558250
0515	H05VV-F 3G1,5	2 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558670
0518	H05VV-F 3G1,5	3 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558267
0519	H05VV-F 3G1,5	3 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558632
0610	H05VV-F 3G2,5	1,5 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558472
0611	H05VV-F 3G2,5	1,5 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558489
0614	H05VV-F 3G2,5	2 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558274
0615	H05VV-F 3G2,5	2 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558298
0618	H05VV-F 3G2,5	3 m	bijela / white	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558281
0619	H05VV-F 3G2,5	3 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558304

MADE IN EUROPE

ŠUKO PRIKLJUČNI KABELO S GUMENIM PLAŠTEM

SCHUKO CONNECTION CABLES WITH RUBBER SHEATH

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0631	H05RR-F 3G2,5	1,5 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558496
0635	H05RR-F 3G2,5	2 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558311
0639	H05RR-F 3G2,5	3 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3859888558328
272-301	H05RR-F 3G1,5	1,5 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3858890448351
272-302	H05RR-F 3G1,5	2 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3858890448368
272-303	H05RR-F 3G1,5	3 m	crna / black	16 A / 250 V~	16 A / 3500 W	250 V~	10	3858890448375

PRIKLJUČNI KABELO ZA ELEKTRIČNE ALATE

CONNECTION CABLES FOR POWER TOOLS

-  Priključni kabeli s kontur utikačem se ugrađuju u električne alate s plastičnim kućištem.
Connection cables with contour plug are installed in power tools with plastic housing.

MADE IN EUROPE

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0282	H05RR-F 2x1	4 m	crna / black	10 A / 250 V~	10 A / 2200 W	250 V~	20	3858883830149
0283	H05RR-F 2x1,5	4 m	crna / black	10 A / 250 V~	10 A / 2200 W	250 V~	10	3858883833225
0285	H05VV-F 2x1	3,5 m	crna / black	10 A / 250 V~	10 A / 2200 W	250 V~	20	38598889306362

TROFAZNI PRIKLJUČNI KABLOVI

CONNECTION CABLES WITH THREE-PHASE POWER PLUG


Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Utikač / Plug	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0713	H05VV-F 5G2,5	1,5 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558564
0715	H05VV-F 5G2,5	2 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558335
0719	H05VV-F 5G2,5	3 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558342
0733	H05RR-F 5G2,5	1,5 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558540
0735	H05RR-F 5G2,5	2 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558359
0739	H05RR-F 5G2,5	3 m	crna / black	16 / 400 V~	16 A / 10.000 W	400 V~	10	3859888558366

MADE IN EUROPE

PRIKLJUČNI KABLOVI ZA STALNI PRIKLJUČAK

CONNECTION CABLES FOR STOVES

MADE IN EUROPE



Slika / Photo	Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
1	0603	H05VV-F 3G2,5	1,5 m	bijela / white	5000 W	250 V~	10	3859888558502
2	0711	H05VV-F 5G2,5	1,5 m	bijela / white	12000 W	400 V~	10	3859888558526
3	272-201	H05VV-F 3G2,5	1,5 m	bijela / white	5000 W	250 V~	10	3858883832389

Produžni kabeli

Teški uvjeti na gradilištu, prelazak automobilske gume preko kabela, izloženost kiši ili pak visokim temperaturama neće utjecati na sigurnost korisnika i trajnost proizvoda jer su artikli iz ove kategorije stvoreni upravo za takve uvjete. Prvenstveno su namijenjeni za profesionalnu upotrebu na gradilištima, u industriji i brodogradnji i ali i ostalim korisnicima koji zahtijevaju najvišu razinu pouzdanosti.

Extension Cables

Difficult working conditions on construction sites, crossing over by car, exposure to rain or high temperatures, all of this will not affect the user's safety and durability of these items because they are made for such conditions. They are primarily intended for professional use on construction sites, in industry and shipbuilding, but also for all others who require the highest level of reliability.



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-131	H07RN-F 5G2,5	5 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890447682
221-132	H07RN-F 5G2,5	10 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890447699
221-133	H07RN-F 5G2,5	20 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890448184
221-101	AT N07V3V3-F 5G2,5	5 m	žuta / yellow	16 A / 10500 W	400 V~	IP44	1	3858890447866
221-102	AT N07V3V3-F 5G2,5	10 m	žuta / yellow	16 A / 10500 W	400 V~	IP44	1	3858890447873
221-103	AT N07V3V3-F 5G2,5	20 m	žuta / yellow	16 A / 10500 W	400 V~	IP44	1	3858890447880
221-111	H07RN-F 5G1,5	5 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890447897
221-112	H07RN-F 5G1,5	10 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890447903
221-113	H07RN-F 5G1,5	20 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890447910



Kabeli s utikačem i natikačem CEE 16A 3P prvenstveno su namijenjeni korištenju u kampovima i marinama za priključivanje kamp kućica i brodova na električnu mrežu. Stupanj zaštite IP44 omogućava korištenje na otvorenom i u vlažnim uvjetima.

Extension cables with CEE 16A 3P plug and socket are primarily intended for use at campsites and in marinas for connecting caravans and boats to the power supply. IP 44 degree of protection enables their use outdoors and under humid conditions.



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-301	H07RN-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448191
221-302	H07RN-F 3G1,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448207
221-303	H07RN-F 3G1,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890447927
221-321	H07RN-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448214
221-322	H07RN-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448221
221-323	H07RN-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448238
221-311	AT N07V3V3-F 3G1,5	5 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890447934
221-312	AT N07V3V3-F 3G1,5	10 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890447941
221-313	AT N07V3V3-F 3G1,5	20 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890447958



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0658	H05RR-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858883833027
0658B	H05RR-F 3G1,5	25 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448276
220-401	H07RN-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448245
220-402	H07RN-F 3G1,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890447965
220-403	H07RN-F 3G1,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890447972
220-411	AT N07V3V3-F 3G1,5	5 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890447989
220-412	AT N07V3V3-F 3G1,5	10 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890447996
220-413	AT N07V3V3-F 3G1,5	20 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890448009
220-421	H07RN-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448252
220-422	H07RN-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448269
220-423	H07RN-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448276



H07RN-F – ova oznaka označava gumeni kabel ali za razliku od **H05RR-F** kabela ima izraženu otpornost na mehanička oštećenja. Naravno, veća fleksibilnost u odnosu na PVC kabel je zadržana.

H07RN-F - this mark indicates a rubber cable, but unlike a **H05RR-F** cable, it has a strong resistance to mechanical damage and, of course, greater flexibility compared to a PVC cable.



AVAILABLE
STANDARDS

SCHUKO / TYPE F

FRENCH / TYPE E

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
220-301	H07RN-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448016
220-302	H07RN-F 3G1,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448023
220-303	H07RN-F 3G1,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858890448030
220-311	H07RN-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP54	1	3858890448047
220-312	H07RN-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP54	1	3858890448054
220-313	H07RN-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP54	1	3858890448061



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-901	H07RN-F 5G2,5	1.5 m	crna / black	16 A / 9500 W	400 V~	IP44	1	3858890448115



AT N07V3V3-F produžni kabeli namijenjeni su za otežane uvjete korištenja kao što su na gradilištima, u industriji, brodogradnji i sl. Prednost **AT N07V3V3-F** kabela u odnosu na standardne PVC kabele je pojačana otpornost na mehanička oštećenja, vodu, ulja, kemikalije te fleksibilnost do -35 °C. Prednost u odnosu na gumene kabele je niža cijena finalnog proizvoda.

AT N07V3V3-F connection cables are designed for operating at heavy-duty conditions such as those on construction sites, in industry, shipbuilding, etc. The advantage of **AT N07V3V3-F** cables over standard PVC cables is enhanced resistance to mechanical damage, water, oil, chemicals and greater flexibility - up to -35 °C. The advantage of AT **N07V3V3-F** cables over rubber cables is lower price of a final product.



AVAILABLE
STANDARDS

SCHUKO / TYPE F

FRENCH / TYPE E

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
220-701	AT N07V3V3-F 3G1,5	5 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890448078
220-702	AT N07V3V3-F 3G1,5	10 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890448085
220-704	AT N07V3V3-F 3G1,5	20 m	žuta / yellow	16 A / 3500 W	250 V~	IP44	1	3858890444575
220-761	AT N07V3V3-F 3G2,5	5 m	žuta / yellow	16 A / 3500 W	250 V~	IP54	1	3858890448092
220-762	AT N07V3V3-F 3G2,5	10 m	žuta / yellow	16 A / 3500 W	250 V~	IP54	1	3858890448108
220-763	AT N07V3V3-F 3G2,5	15 m	žuta / yellow	16 A / 3500 W	250 V~	IP54	1	3858890444599
220-764	AT N07V3V3-F 3G2,5	20 m	žuta / yellow	16 A / 3500 W	250 V~	IP54	1	3858890444605

Adapter za pretvaranje CEE standarda u šuko standard.
Plug adapter for converting CEE to Schuko standard.

MADE IN EUROPE



AVAILABLE STANDARDS		SCHUKO / TYPE F		FRENCH / TYPE E	

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-212	H07RN-F 3G1,5	1.5 m	crna / black	16 A / 3500 W	250 V~	IP44	10	3858890448290

Adapter za pretvaranje šuko standarda u CEE standard.
Plug adapter for converting Schuko to CEE standard.

MADE IN EUROPE



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-202	H07RN-F 3G1,5	1.5	crna / black	16 A / 3500 W	250 V~	IP44	10	3858890448283

MADE IN EUROPE



AVAILABLE STANDARDS		SCHUKO / TYPE F		FRENCH / TYPE E	

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	Diferencijalna struja / Tripping current	EAN
222-201	H07RN-F 3G1,5	1.5 m	crna / black	16 A	250 V~	IP20	1	30 mA	3858890448122

MADE IN EUROPE



AVAILABLE STANDARDS		SCHUKO / TYPE F		FRENCH / TYPE E	

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	Diferencijalna struja / Tripping current	EAN
222-101	H07RN-F 3G1,5	1.5 m	crna / black	16 A	250 V~	IP20	1	30 mA	3858890448139



Commel MARINKO grupa proizvoda je opremljena specijalnim MarinFlex kablom otpornim na abrazivna djelovanja morske vode. MarinFlex kabl moguće je koristiti u uvjetima trajnog ili povremenog kontakta s morskom vodom, a odlikuju ga izvrsna fleksibilnost i otpornost na visoke i niske temperature. Posebno je pogodan za električni priključak plovila u marinama jer je jednostavan za održavanje, lako se čisti i ne ostavlja tragove na površinama.

The Commel MARINKO product group is equipped with a special MarinFlex cable resistant to the abrasive action of sea water. The MarinFlex cable can be used in conditions of permanent or occasional contact with sea water, and it has excellent flexibility and resistance to high and low temperatures. It is especially suitable for the electrical connection of boats in the marinas because it is easy to maintain, easy to clean and leaves no traces on the surfaces.



Upotreba u marinama
Suitable for use in Marinas



Upotreba u ribogojilištima
Suitable for use in Fish Farms



Upotreba za električni priključak plovila
Boat electrical connection

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-331	MarinFlex 3G1,5	5 m	narančasta / orange	16 A / 3500 W	250 V~	IP44	1	3858890449631
221-332	MarinFlex 3G1,5	10 m	narančasta / orange	16 A / 3500 W	250 V~	IP44	1	3858890449648
221-333	MarinFlex 3G1,5	20 m	narančasta / orange	16 A / 3500 W	250 V~	IP44	1	3858890449655



 Adapter za pretvaranje CEE standarda u šuko standard.
Plug adapter for converting CEE to Schuko standard.

Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-213	MarinFlex 3G1,5	1,5 m	narančasta / orange	16 A / 3500 W	250 V~	IP44	1	3858890449679



 Adapter za pretvaranje šuko standarda u CEE standard.
Plug adapter for converting Schuko to CEE standard.



Šifra / Art. No.	Kabel / Cable	Dužina kabela / Cable length	Boja kabela / Cable color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-203	MarinFlex 3G1,5	1,5 m	narančasta / orange	16 A / 3500 W	250 V~	IP44	1	3858890449662

HOBBY LINE

Produžni kabe

Kada Vam priključak na električnu energiju nije nadohvat ruke, posegnite za Commel produžnim kabe





Extension Cables

When the power supply is not close at hand, reach for the Commel extension cable and bring the power to your appliances. Different lengths, cross sections and cable colors cover all areas of application in your home or workshop.

Commel®

HOBBY LINE

PRODUŽNI KABE



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
221-121	H05VV-F 5G1,5	5 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890448146
0744	H05VV-F 5G1,5	10 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858883834277
221-123	H05VV-F 5G1,5	20 m	crna / black	16 A / 10500 W	400 V~	IP44	1	3858890448153



H05RR-F – oznaka označava gumeni kabe. Glavna prednost u odnosu na PVC kabe je puno veća fleksibilnost, pogotovo na temperaturama ispod 0°C.

H05RR-F - mark for a rubber cable. Its main advantage over a PVC cable is much greater flexibility, especially at temperatures below 0°C.



AVAILABLE STANDARDS	 SCHUKO / TYPE F	 FRENCH / TYPE E
------------------------	---	---

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
0644	H05RR-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858883831672
0645	H05RR-F 3G1,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858883831696
0647	H05RR-F 3G1,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3858883831733
0650	H05RR-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3859888761728
0651	H05RR-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3859888761742
0652	H05RR-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP44	1	3859888761766



AVAILABLE STANDARDS


 SCHUKO / TYPE F
  FRENCH / TYPE E
  BRITISH / TYPE G

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
220-110	H05VV-F 3G1	10 m	crvena / red	10 A / 2200 W	250 V~	IP20	1	3858890448160
220-115	H05VV-F 3G1	15 m	crvena / red	10 A / 2200 W	250 V~	IP20	1	3858883836080
0872A	H05VV-F 3G1	20 m	crvena / red	10 A / 2200 W	250 V~	IP20	1	3858883830637
0872	H05VV-F 3G1	25 m	crvena / red	10 A / 2200 W	250 V~	IP20	1	3858883830248
220-205	H05VV-F 3G1,5	5 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858890449778
220-210	H05VV-F 3G1,5	10 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858890449785
220-215	H05VV-F 3G1,5	15 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858890440713
220-220	H05VV-F 3G1,5	20 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858890440720
0871	H05VV-F 3G1,5	25 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858883830224
220-230	H05VV-F 3G1,5	30 m	crvena / red	16 A / 3500 W	250 V~	IP20	1	3858890449792
220-151	H05VV-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449402
220-152	H05VV-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449419
220-153	H05VV-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449426
220-171	H05RR-F 3G1,5	5 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449464
220-172	H05RR-F 3G1,5	10 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449471
220-173	H05RR-F 3G1,5	20 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449488
220-181	H05RR-F 3G2,5	5 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449433
220-182	H05RR-F 3G2,5	10 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449440
220-183	H05RR-F 3G2,5	20 m	crna / black	16 A / 3500 W	250 V~	IP20	1	3858890449457

MADE IN EUROPE

Bijeli produžni kabeli s PVC plaštom namijenjeni su kućnoj upotrebi. Maksimalno opterećenje od 16 A omogućava priključivanje aparata snage do 3500 W. Utičnice su opremljene zaštitom od kontakta (Zaštita od direktnog kontakta).

White connection cables with PVC sheath are intended for home use. The maximum load of 16 A allows you to manage appliances with power up to 3500 W. The sockets are equipped with contact protection (Direct contact protection).



AVAILABLE STANDARDS

 SCHUKO / TYPE F
  FRENCH / TYPE E
  BRITISH / TYPE G

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
220-502	H05VV-F 3G1	2 m	bijela / white	16 A / 3500 W	250 V~	IP20	10	3858890442861
220-504	H05VV-F 3G1,5	4 m	bijela / white	16 A / 3500 W	250 V~	IP20	10	3858890442878
220-508	H05VV-F 3G1,5	8 m	bijela / white	16 A / 3500 W	250 V~	IP20	10	3858890442885

MADE IN EUROPE



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
223-101	H03VVH2-F 2x0,75	2 m	bijela / white	2,5 A / 500 W	250 V~	IP20	20	3858890445985
223-102	H03VVH2-F 2x0,75	4 m	bijela / white	2,5 A / 500 W	250 V~	IP20	20	3858890448177

ZAŠTITNA KUTIJA ZA SPAJANJE KABELA SAFE BOX FOR CABLE CONNECTION

Šifra / Art. No.	Stupanj zaštite / IP grade	EAN
366-101	IP44	3858890441703

- omogućava vodootporni spoj, sprječava razdvajanje utikača od utičnice, mogućnost montaže na zid, 5 kopči za sigurno zatvaranje
- allows a waterproof connection, prevents unplugging, possibility of mounting on the wall, 5 clips for safe closing



DRŽAČ KABELA CABLE HOLDER

Šifra / Art. No.	Maksimalna nosivost / Max. load	Materijal / Material	EAN
366-105	40 kg	LDPE	3858890449624



Prenaponska zaštita

Kada obična prenosiva utičnica ne zadovoljava Vaše sigurnosne standarde i želite dodatno zaštititi svoje električne uređaje preporučujemo upotrebu prenosivih utičnica s prenaponskom zaštitom. Mislite li da je pametno kupiti TV, PC ili neki drugi skupi aparat, a ne kupiti prenaponsku zaštitu za mali djelić vrijednosti tih aparata? Odluka je na Vama ali svaki put za grmljavinskog nevremena razmišljati ćete o mogućoj šteti od udara groma u Vašu električnu mrežu. Prenaponska zaštita ima funkciju preuzeti energiju udara groma i prekinuti strujni krug prema Vašim električnim aparatima.




Surge Protection

When the standard socket outlet does not meet your safety standards and you want to protect further your electrical appliances, we recommend the use of socket outlets with surge protection. Do you think it is wise to buy a TV, PC or other expensive appliance and not buy surge protection for a small fraction of the value of these appliances? It is up to you, but each time during thunderstorms you will be thinking about the possible damage the lightning strike can cause to your appliances. Surge protection is designed to protect appliances against electrical surges and spikes, including those caused by lightning. It attempts to limit the voltage supplied to an appliance by either blocking or shorting to ground any unwanted voltages above a safe threshold.



PRENAPONSKA ZAŠTITA | SURGE PROTECTION

- Zaštita od preopterećenja (termoprekidač) – prekida strujni krug u slučaju pregrijavanja utičnice uzrokovanog priključivanjem aparata ukupne snage veće od 3500 W**
Overload protection (thermo switch) – cuts off electric current in case of overheating of the socket outlet caused by plugging in appliances with total power greater than 3500 W
- Zaštita od prenapona – štiti priključene uređaje od prenapona uzrokovanog udarom groma u električnu mrežu**
Surge protection - protects the appliances against electrical surges and spikes, including those caused by lightning
- 8 šuko utičnice + 2 USB punjača**
8 Schuko sockets + 2 USB chargers



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	USB	Kom./kutija / Pcs/ctn	EAN
380-107	H05VV-F 3G1,5	3 m	8 x 230 V ~ / 16 A	16 A / 3500 W	250 V~	5V DC 2,1 A	10	3858883839180

- Zaštita od preopterećenja (termoprekidač) – prekida strujni krug u slučaju pregrijavanja utičnice uzrokovanog priključivanjem aparata ukupne snage veće od 3500 W**
Overload protection (thermo switch) – cuts off electric current in case of overheating of the socket outlet caused by plugging in appliances with total power greater than 3500 W
- Zaštita od prenapona – štiti priključene uređaje od prenapona uzrokovanog udarom groma u električnu mrežu**
Surge protection - protects the appliances against electrical surges and spikes, including those caused by lightning



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
380-106	H05VV-F 3G1,5	3 m	5 x 230 V ~ / 16 A	16 A / 3500 W	250 V~	20	3858890441260

- Zaštita od prenapona – štiti priključene uređaje od prenapona uzrokovanog udarom groma u električnu mrežu**
Surge protection - protects the appliances against electrical surges and spikes, including those caused by lightning



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
380-105	H05VV-F 3G1,5	1,5 m	6 x 230 V ~ / 16 A	16 A / 3500 W	250 V~	40	3858883838800

Prenosive utičnice

Konstrukcijom i odabirom samogasivih materijala zajamčena je sigurnost pri korištenju. Dvopolna osvijetljena sklopka odvaja na siguran način trošila od mreže. Sve utičnice su opremljene zaštitom od direktnog dodira (Zaštita od direktnog kontakta).

Extension Sockets

The construction and self-extinguishing materials guarantee the safety of use. The two-pole illuminated switch safely disconnects appliances from the power supply. All sockets are equipped with contact protection (Direct contact protection).



PRENOSIVE UTIČNICE | EXTENSION SOCKETS



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0802	H05VV-F 3G1	1,4 m	3	16 A / 3500 W	250 V~	10	3859888558014
0804	H05VV-F 3G1,5	3 m	3	16 A / 3500 W	250 V~	10	3859888558021
0806	H05VV-F 3G1,5	5 m	3	16 A / 3500 W	250 V~	10	3859888558038
0808	H05VV-F 3G1,5	10 m	3	16 A / 3500 W	250 V~	10	3859888558045
232-501	H05VV-F 3G1	1,4 m	5	16 A / 3500 W	250 V~	10	3858883835809
232-502	H05VV-F 3G1,5	3 m	5	16 A / 3500 W	250 V~	10	3858883835465
232-503	H05VV-F 3G1,5	5 m	5	16 A / 3500 W	250 V~	10	3858883835472

 **Zaštita od direktnog kontakta**
Direct contact protection

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0814	H05VV-F 3G1	1,4 m	3	16 A / 3500 W	250 V~	10	3859889306546
0815	H05VV-F 3G1,5	3 m	3	16 A / 3500 W	250 V~	10	3858883830415
0816	H05VV-F 3G1,5	5 m	3	16 A / 3500 W	250 V~	10	3859889306560
0817	H05VV-F 3G1	1,4 m	5	16 A / 3500 W	250 V~	10	3859889306522
232-504	H05VV-F 3G1,5	3 m	5	16 A / 3500 W	250 V~	10	3858883836127
232-505	H05VV-F 3G1,5	5 m	5	16 A / 3500 W	250 V~	10	3858883836134
0838	H05VV-F 3G1	1,4 m	6	16 A / 3500 W	250 V~	10	3859889306607
0837	H05VV-F 3G1,5	3 m	6	16 A / 3500 W	250 V~	10	3858883830439
0839	H05VV-F 3G1,5	5 m	6	16 A / 3500 W	250 V~	10	3859889306584

 **Dvopolna sklopka**
Two-pole illuminated switch

 **Zaštita od direktnog kontakta**
Direct contact protection



 **Dvopolna sklopka**
Two-pole illuminated switch

 **Zaštita od direktnog kontakta**
Direct contact protection



Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
0843	H05VV-F 3G1	1,4 m	4 x EURO 4 x ŠUKO / SCHUKO	2,5 A / 16 A	250 V~	10	3859889306621



 **Zaštita od direktnog kontakta**
Direct contact protection

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
232-321	H05VV-F 3G1	1,4 m	3	16 A / 3500 W	250 V~	10	3858890446913
232-322	H05VV-F 3G1,5	3 m	3	16 A / 3500 W	250 V~	10	3858890446920
232-521	H05VV-F 3G1	1,4 m	5	16 A / 3500 W	250 V~	10	3858890447507
232-522	H05VV-F 3G1,5	3 m	5	16 A / 3500 W	250 V~	10	3858890447514



 **Dvopolna sklopka**
Two-pole illuminated switch

 **Zaštita od direktnog kontakta**
Direct contact protection

Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
232-324	H05VV-F 3G1	1,4 m	3	16 A / 3500 W	250 V~	10	3858890446937
232-325	H05VV-F 3G1,5	3 m	3	16 A / 3500 W	250 V~	10	3858890446944
232-524	H05VV-F 3G1	1,4 m	5	16 A / 3500 W	250 V~	10	3858890447521
232-525	H05VV-F 3G1,5	3 m	5	16 A / 3500 W	250 V~	10	3858890447538

POP UP UTIČNICE
POP UP SOCKETS



 **Svjetlosni indikator napona**
Power indicator light

 **3 šuko utičnice**
3 Schuko sockets

 **Dvopolna sklopka**
Two-pole illuminated switch

 **3 šuko utičnice + 2 USB punjača**
3 Schuko sockets + 2 USB chargers


Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	USB	Kom./kutija / Pcs/ctn	EAN
232-181	H05VV-F 3G1,5	1,8 m	3	16 A / 3500 W	220-240 V~ 50/60Hz	-	20	3856024402217
234-181	H05VV-F 3G1,5	1,8 m	3	16 A / 3500 W	220-240 V~ 50/60Hz	2.1 A 5V	20	3856024402224

 **Svjetlosni indikator napona**
Power indicator light



 **3 šuko utičnice + 2 USB punjača**
3 Schuko sockets + 2 USB chargers

Šifra / Art. No.	Boja / Color	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	USB	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
234-401	bijela / white	H05VV-F 3G1	1,4 m	3	5V DC 2,1 A	16 A / 3500 W	250 V~	10	3856024403542
232-402	bijela / white	H05VV-F 3G1,5	3 m	3	5V DC 2,1 A	16 A / 3500 W	250 V~	10	3856024403559
232-411	crna / black	H05VV-F 3G1	1,4 m	3	5V DC 2,1 A	16 A / 3500 W	250 V~	10	3856024403566
232-412	crna / black	H05VV-F 3G1,5	3 m	3	5V DC 2,1 A	16 A / 3500 W	250 V~	10	3856024403573



 **4 šuko utičnice + 2 USB punjača**
4 Schuko sockets + 2 USB chargers

 **Svjetlosni indikator napona**
Power indicator light

 **Nosač za montažu na zid ili stol**
Bracket for wall or table mounting


Šifra / Art. No.	Kabel / Cable	Dužina / Length	Broj utičnica / Number of sockets	Max. opterećenje / Max. load	Nazivni napon / Voltage	USB	Kom./kutija / Pcs/ctn	EAN
234-161	H05VV-F 3G1,5	1,4 m	4	16 A / 3500 W	250 V~	5V DC 2,1 A	16	3858890446340

Industrijski utikači,
natikači i utičnice


CEE Plugs, Connectors
and Sockets



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-101	16 A	400 V~	4P	IP44	1	3858890444100
280-102	32 A	400 V~	4P	IP44	1	3858890444117
280-103	16 A	400 V~	5P	IP44	1	3858890444124
280-104	32 A	400 V~	5P	IP44	1	3858890444131
280-105	63 A	400 V~	5P	IP44	1	3858890444148




Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-113	16 A	400 V~	5P	IP67	1	3856024403863
280-114	32 A	400 V~	5P	IP67	1	3856024403870



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
281-101	16 A	400 V~	4P	IP44	1	3858890444155
281-102	32 A	400 V~	4P	IP44	1	3858890444162
281-103	16 A	400 V~	5P	IP44	1	3858890444179
281-104	32 A	400 V~	5P	IP44	1	3858890444186
281-105	63 A	400 V~	5P	IP44	1	3858890444193

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
281-113	16 A	400 V~	5P	IP67	1	3856024403887
281-114	32 A	400 V~	5P	IP67	1	3856024403894




Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-501	16 A	400 V~	5P	IP44	1	3858890444254
280-502	32 A	400 V~	5P	IP44	1	3858890444261



 **Izmjena faze**
Phase inverter



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-301	16 A	400 V~	5P	IP44	1	3858890444278
280-302	32 A	400 V~	5P	IP44	1	3858890444285




Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
282-551	16 A	250/400 V~	5P	IP44	1	3858890444292




Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
282-301	16 A	400 V~	5P	IP44	1	3858890444308



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
282-501	16 A	400 V~	4P	IP44	1	3858890444209
282-502	32 A	400 V~	4P	IP44	1	3858890444216
282-503	16 A	400 V~	5P	IP44	1	3858890444223
282-504	32 A	400 V~	5P	IP44	1	3858890444230
282-505	63 A	400 V~	5P	IP44	1	3858890444247





Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-201	16 A	250 V~	3P	IP44	1	3858890444315
280-202	32 A	250 V~	3P	IP44	1	3856024400145

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
280-211	16 A	250 V~	3P	IP67	1	3856024403900



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
281-201	16 A	250 V~	3P	IP44	1	3858890444322
281-202	32 A	250 V~	3P	IP44	1	3856024400152



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
281-211	16 A	250 V~	3P	IP67	1	3856024403917



Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
282-511	16 A	250 V~	3P	IP44	1	3858890444339

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
282-311	16 A	250 V~	3P	IP44	1	3858890444346




 Adapter za pretvaranje CEE standarda u šuko+talijanski standard
Plug adapter for converting CEE to Schuko+Italian standard

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
284-101	16 A	250 V~	3P	IP20	1	3856024403405



 Adapter za pretvaranje šuko standarda u CEE standard.
Plug adapter for converting Schuko to CEE standard

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Polovi / Poles	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
284-102	16 A	250 V~	3P	IP20	10	3856024403412



Utikači, natikači i utičnice

Različite izvedbe s ravnim ili kutnim ulazom kabela, stupnjem zaštite IP44 ili IP20 te kućištima od plastike ili gume pokrivaju sva područja primjene Commel utikača i natikača. Vijčani prihvat vodiča osigurava zaštitu od izvlačenja kabela i jamči sigurnost pri upotrebi.

Plugs, Connectors and Sockets

Various designs with straight or angular cable entry, IP44 or IP20 degree of protection, plastic or rubber housing, cover all areas of application of the Commel plugs and sockets. Screw terminals provide protection against cable pulling and guarantee safety when used.




Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-601	bijela/white	2,5 A	250 V~	IP20	10	3858890442670
290-602	crna/black	2,5 A	250 V~	IP20	10	3858890442687

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-601	bijela/white	2,5 A	250 V~	IP20	10	3858890442694
291-602	crna/black	2,5 A	250 V~	IP20	10	3858890442700

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-101	bijela/white	16 A	250 V~	IP20	10	3858883833928
290-102	crna/black	16 A	250 V~	IP20	10	3858883833935

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-201	bijela/white	16 A	250 V~	IP20	10	3858883833942
290-202	crna/black	16 A	250 V~	IP20	10	3858883833959



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-101	bijela/white	16 A	250 V~	IP20	10	3858883833966
291-102	crna/black	16 A	250 V~	IP20	10	3858883833973

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-201	bijela/white	16 A	250 V~	IP20	10	3858883833980
291-202	crna/black	16 A	250 V~	IP20	10	3858883833997




Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-501	bijela/white	16 A	250 V~	IP20	10	3858890442625
290-502	crna/black	16 A	250 V~	IP20	10	3858890442649



 **Gumirani**
Rubber

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-301	crna/black	16 A	250 V~	IP44	10	3858890444353



 **Gumirani**
Rubber

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-302	crna/black	16 A	250 V~	IP44	10	3858883831450



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-308	crna/black	16 A	250 V~	IP54	30	3856024402293



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
290-305	crveno-crna / red-black	16 A	250 V~	IP54	10	3858890446838
290-306	sivo-crna / grey-black	16 A	250 V~	IP54	10	3858890446852



 **Gumirani**
Rubber

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-301	crna/black	16 A	250 V~	IP20	10	3858890444360



 Gumirani
Rubber

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-304	crna/black	16 A	250 V~	IP44	10	3858890448405



 Gumirani
Rubber

Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-302	crna/black	16 A	250 V~	IP44	10	3858883831467



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-308	crna/black	16 A	250 V~	IP20	20	3856024402309



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-309	crna/black	16 A	250 V~	IP54	20	3856024402316



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
291-305	crveno-crna / red-black	16 A	250 V~	IP54	10	3858890446845
291-306	sivo-crna / grey-black	16 A	250 V~	IP54	10	3858890446869



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
6350	crna/black	16 A	400 V~	IP20	20	3858883838015



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
292-101	crvena - crna/red - black	16 A	250 V~	IP54	1	3858890444469



Šifra / Art. No.	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
293-701	bijela/white	2,5 A	250 V~	10	3858890445466
293-702	crna/black	2,5 A	250 V~	10	3858890445473



Razdjelnici, adapteri i blokade


Kada u stanu imate premali broj utičnih mjesta ili ste dobili neočekivane goste sa drugog kraja svijeta koji ne mogu priključiti svoj punjač za mobitel ili prijenosno računalo na Vašu električnu mrežu ili imate malu djecu koja guraju svoje prstiće u sve pa tako i u električne utičnice...ova kategorija rješava sve takve probleme.



Adaptors and Direct contact protection

When you have a small number of sockets at home, or you get unexpected guests from the other side of the world who can not plug in their mobile or laptop charger into your power supply, or you have small children sticking their fingers into everything including electrical sockets... This category solves all such problems.

Commel®



Šifra / Art. No.	Broj utičnica / Number of sockets	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
6338-1	2	bijela / white	16 A / 3500 W	250 V~	10	3858883838404
6338-2	2	crna / black	16 A / 3500 W	250 V~	10	3858883838411
240-103	2	transparentna / transparent	16 A / 3500 W	250 V~	10	3858890448313
6338-3	3	bijela / white	16 A / 3500 W	250 V~	10	3858883838428
6338-4	3	crna / black	16 A / 3500 W	250 V~	10	3858883838435
240-113	3	transparentna / transparent	16 A / 3500 W	250 V~	10	3858890448320



Šifra / Art. No.	Broj utičnica / Number of sockets	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
49111-1	3	bijela / white	2,5 A / 16 A	250 V~	10	3858883838541
49112-2	3	crna / black	2,5 A / 16 A	250 V~	10	3858883838510



Utičnice i razdjelnici sa sklopkom su praktično rješenje za uključivanje i isključivanje priključenih uređaja jednostavnim pritiskom prekidača. Savršenu primjenu pronalaze u kućanstvu za prekidanje napajanja elektroničkih uređaja za vrijeme mirovanja. Na taj način sprječavamo neželjenu potrošnju električne energije dok se uređaji ne koriste.

Sockets and adapters with a switch are a practical solution for turning on and off connected appliances by simply pressing the switch. Perfect application is found in the household for cutting off the power to appliances during their idle time. This prevents unwanted power consumption while the appliances are not in use.

Slika / Photo	Šifra / Art. No.	Broj utičnica / Number of sockets	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
1	240-301	1	bijela / white	16 A	250 V~	10	3858890441512
2	240-302	2	bijela / white	16 A	250 V~	10	3858890441505
3	240-303	3	bijela / white	2,5 A / 16 A	250 V~	10	3858890441499
4	240-305	2	bijela / white	16 A	250 V~	10	3856024402910
5	240-306	3	bijela / white	2,5 A / 16 A	250 V~	10	3856024402927



1



2




3



4



5



Šifra / Art. No.	Broj utičnica / Number of sockets	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
240-501	3	crna / black	16 A	250 V~	IP44	10	3858890443073

- Omogućuje priključivanje utikača različitih standarda u šuko utičnicu
Allows connection of different plug standards to a Schuko socket
- Putni adapter ne pretvara napone
Travel adapter does not convert voltages
- Zaštita od direktnog kontakta
Direct contact protection
- Visoka stijenka koja onemogućuje uključivanje samo jednog pina utikača
A high wall prevents the accidental plugging of just one plug pin



Šifra / Art. No.	Broj utičnica / Number of sockets	Boja / Color	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
480-102	1	bijela / white	10 A	250 V~	1	3858890444834

ZAŠTITA OD DIREKTOG KONTAKTA DIRECT CONTACT PROTECTION

- Jednostavno postavljanje u bilo koju šuko utičnicu
Easy installation in any Schuko socket
- 10 komada u pakiranju
10 pieces in packaging



Šifra / Art. No.	Boja / Color	Kom./kutija / Pcs/ctn	EAN
48109-1	bijela / white	10	3858883838619

Kućna automatizacija

Živimo u doba kada je sve automatizirano ili obavlja svoju zadaću pritiskom samo jedne tipke. Commel kućna automatizacija namijenjena je olakšavanju dnevnih zadataka u kući, uredu i vrtu, ali i uštedi u kućanstvu.

Home Automation

We live in an age when everything is automated or performs its task by pressing just one button. Commel home automation is intended to facilitate the daily tasks in the home, office and garden, but also to make household savings.

Commel®



Commel IoT App download



WIFI UTIČNICA WIFI SOCKET

- Upravljanje električnim uređajima na daljinu putem pametnog telefona ili tableta bez obzira gdje se nalazite**
 Use smartphone or tablet to control your electrical appliances remotely from anywhere
- Funkcija programatora – za jednostavno podešavanje automatskog uključivanja i isključivanja**
 Timer function – for easy setting of auto power on and off

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	WIFI	Kom./kutija / Pcs/ctn	EAN
265-306	16 A / 3500 W	230 V~	2,4 GHz, 802.11b/g/n; +16dBm	60	3856024400046



Commel smart home



Commel IoT
App
download



WIFI PREKIDAČ WIFI SWITCH

- Upravljaite pametnim prekidačima na daljinu putem pametnog telefona ili tableta bez obzira gdje se nalazite
Use smartphone or tablet to control your smart switch remotely from anywhere
- Funkcija programatora – za jednostavno podešavanje automatskog uključivanja i isključivanja
Timer function – for easy setting of auto power on and off

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	WIFI	Kom./kutija / Pcs/ctn	Stupanj zaštite / IP grade	EAN
265-501	100 W / 800 W	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	60	IP20	3856024400053
265-502	100 W / 800 W	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	60	IP20	3856024400060

max. 800 W

max. 100 W



Commel smart home





Commel IoT
App
download



WIFI ŽARULJA WIFI LIGHT BULB

Šifra / Art. No.	Snaga / Power	Svijetlosti tok / Luminous flux	Temperatura svjetla / Color temperature	Životni vijek / Lifespan	Nazivni napon / Input voltage	WIFI	Baza / Base	Kom./kutija / Pcs/ctn	Stupanj zaštite / IP grade	EAN
305-701	9 W	820 lm	3000-6500 K	25.000 h	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	E27	5	IP20	3856024402644



WIFI SMART PLAFONJERA
WIFI SMART CEILING LIGHT



Commel IoT
App
download



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Nazivni napon / Input voltage	WiFi	Kom./kutija / Pcs/ctn	Stupanj zaštite / IP grade	EAN
407-801	1 x 12 W	1 x 1200 lm	3000-6000 K	25.000 h	260 mm	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	20	IP20	3856024403603
407-802	1 x 24 W	1 x 2500 lm	3000-6000 K	25.000 h	380 mm	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	10	IP20	3856024403610
407-803	1 x 36 W	1 x 3800 lm	3000-6000 K	25.000 h	490 mm	220-240 V~	2,4 GHz, 802.11b/g/n; +16dBm	10	IP20	3856024403627

WARM WHITE - COOL WHITE
3000K 6000 K


COLOR CHANGE



Commel




Commel IoT
App
download



WIFI SMART KUTNA SVJETILJKA
WIFI SMART CORNER LAMP

COLOR CHANGE

Šifra / Art. No.	Snaga / Power	Visina svjetiljke / Lamp height	Nazivni napon / Input voltage	WiFi	Kom./kutija / Pcs/ctn	Stupanj zaštite / IP grade	EAN
405-501	12 W	1,4 m	110-240 V DC 12 V	2,4 GHz, 802.11b/g/n; +16dBm	8	IP20	3856024403634



Commel

DIGITALNI PROGRAMATOR, TJEDNI

DIGITAL TIMER, WEEKLY

- 20 ON/OFF programa
20 ON/OFF programs
- Zaštita od direktnog kontakta
Direct contact protection
- Minimalni vremenski interval: 1 minuta
Minimum time interval: 1 minute
- Memorija postavki u slučaju nestanka struje
Memory that saves the settings in case of power failure
- Odbrojanje vremena
Countdown timer
- 12-satni ili 24-satni prikaz
12-hour or 24-hour display
- LCD zaslon
LCD screen

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
261-103	16 A / 3500 W	230 V~	10	3858890448467



MEHANIČKI PROGRAMATOR, DNEVNI

MECHANICAL DAILY TIMER

- 24-satno programiranje
24-hour programming
- Do 48 uključivanja/isključivanja dnevno
Up to 48 times on/off daily
- Minimalni vremenski interval: 30 minuta
Minimum time interval: 30 minutes
- Zaštita od direktnog kontakta
Direct contact protection

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
90821	16 A / 3500 W	230 V~	10	3858883838480



MEHANIČKI PROGRAMATOR, DNEVNI

MECHANICAL DAILY TIMER

- 24-satno programiranje
24-hour programming
- Do 48 uključivanja/isključivanja dnevno
Up to 48 times on/off daily
- Minimalni vremenski interval: 30 minuta
Minimum time interval: 30 minutes
- Zaštita od direktnog kontakta
Direct contact protection
- IP44 stupanj zaštite
IP44 degree of protection

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	Stupanj zaštite / IP grade	EAN
260-201	16 A / 3500 W	230 V~	10	IP44	3858890444612



MJERAČ POTROŠNJE ELEKTRIČNE ENERGIJE

POWER METER

- Veliki LCD zaslon
Large LCD screen
- Dvotarifni
Dual tariff
- Mogućnost mjerenja sljedećih parametara:
- snaga priključenog aparata (W)
- napon utičnice (V)
- frekvencija (Hz)
- struja (A)
- faktor snage (PF)e
- Zaštita od direktnog kontakta
Direct contact protection
- Izračun cijene utrošene energije
Calculation of energy consumption

Ability to measure the following parameters:
- power of connected appliance (W)
- socket voltage (V)
- frequency (Hz)
- electric current (A)
- power factor (PF)

Šifra / Art. No.	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
430-106	16 A / 3680 W	230 V~	50	385602402576



UTIČNICE S DALJINSKIM UPRAVLJAČEM

REMOTE CONTROL SOCKETS

- Domet: 30 m
Remote range: 30 m
- Automatsko povezivanje
Automatic connection
- Zaštita od direktnog kontakta
Direct contact protection



	Šifra / Art. No.	Domet / Range	Max. opterećenje / Max. load	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
1	265-115	30 m	13 A / 3000 W	230 V~	10	3858890448474
2	265-116	30 m	13 A / 3000 W	230 V~	10	3858890448481



Multimetri i ispitivači napona

Kada je potrebno izmjeriti napon električne mreže, provjeriti otpor ili ispravnost vodiča, ova kategorija nudi svakom kućnom majstoru sve što mu je potrebno.

Multimeters and Voltage Testers

This category offers every handyman all he needs to measure the voltage of the power supply, check the resistance or functionality of the lead wires.



DIGITALNI MULTIMETAR
DIGITAL MULTIMETER



- CAT III; zaslon s 3 ½ znamenke (maksimalni prikaz: 1999); provjera dioda i provodljivosti**
CAT III; 3 ½ digit display (max. reading: 1999); Testing diode and continuity

- Indikacija prazne baterije; mjerni vodovi u pakiranju**
Low battery indication; Test leads included

Šifra / Art. No.	AC napon / AC voltage	DC napon / DC voltage	DC struja / DC current	Otpor / Resistance	Baterija u pakiranju / Battery included	Kom./kutija / Pcs/ctn	EAN
450-102	200 V - 300 V	200 mV - 300 V	20 µA - 10 A	200 Ω - 2 MΩ	1 x 9 V DC	60	3858890443769



- CAT III; zaslon s 3 ½ znamenke (maksimalni prikaz: 1999); provjera dioda**
CAT III; 3 ½ digit display (max. reading: 1999); Testing diode

- Test baterija (1,5 V i 9 V); Indikacija prazne baterije**
Battery test (1.5 V i 9 V); Low battery indication

Šifra / Art. No.	AC napon / AC voltage	DC napon / DC voltage	DC struja / DC current	Otpor / Resistance	Baterija u pakiranju / Battery included	Kom./kutija / Pcs/ctn	EAN
450-103	200 V - 300 V	200 mV - 300 V	2000 µA - 200 mA	200 Ω - 2000 kΩ	1 x 12 V, 23 A	42	3858890443776


DIGITALNA STRUJNA KLIJEŠTA
DIGITAL CLAMP METER



- CAT III; zaslon s 3 ½ znamenke (maksimalni prikaz: 1999)**
CAT III; 3 ½ digit display (max. reading: 1999)
- Indikacija prazne baterije; mjerni vodovi u pakiranju**
Low battery indication; Test leads included
- Funkcija zadržavanja podataka; Zaštita od preopterećenja**
Data-hold function; Overload protection

Šifra / Art. No.	AC napon / AC voltage	DC napon / DC voltage	AC struja / AC current	Opor / Resistance	Baterija u pakiranju / Battery included	Kom./kutija / Pcs/ctn	EAN
450-201	300 V	300 V	20 A - 400 A	2000 Ω - 200 kΩ	3 x 3V, CR2032	60	3856024403658

DETEKTOR NAPONA - BEZKONTAKTNI
NON-CONTACT VOLTAGE DETECTOR



- CAT III; sigurna detekcija napona - bez kontakta**
CAT III; Safe, non-contact voltage detection
- Svjetlosna i zvučna signalizacija**
LED and buzzer indication

Šifra / Art. No.	Raspon napona/ Voltage range	Baterija u pakiranju / Batteries included	Kom./kutija / Pcs/ctn	EAN
445-201	70-1000 V~ 50/60 Hz	2 x 1,5 V, AAA	60	3858890443752



ISPITIVAČ NAPONA
VOLTAGE TESTER

- CAT III; LED indikacija u visini izmjerene napona**
CAT III; LED lights up to the voltage reading
- Indikacija polariteta DC napona**
DC voltage polarity indication

Šifra / Art. No.	Raspon napona/ Voltage range	Frekvencija / Frequency	Baterija u pakiranju / Batteries included	Kom./kutija / Pcs/ctn	EAN
445-101	6 V / 12 V / 24 V / 50 V / 120 V / 230 V / 400 V	50-60 Hz	2 x LR44 1.5 V	48	3858890443745



ISPITIVAČI NAPONA
VOLTAGE TESTERS

Šifra / Art. No.	Dužina / Length	Raspon napona / Voltage range	Kom./kutija / Pcs/ctn	EAN
445-301	140 mm	200 - 250 V ~	20	3856024401845

Šifra / Art. No.	Dužina / Length	Raspon napona / Voltage range	Kom./kutija / Pcs/ctn	EAN
445-302	190 mm	200 - 250 V ~	20	3856024401852



Zvonca

Commel električna i bežična zvonca namijenjena su za kućnu upotrebu ali isto tako mogu naći svoju primjenu i u drugim područjima. Veliki domet bežičnih zvonaca garantira jasnu i nesmetanu komunikaciju između tipkala i samog zvonca. Širok izbor dizajna omogućava svakom kupcu pronaći zvonce po svom ukusu koje će mu ujedno uljepšavati unutarnji prostor.



Doorbells

Commel electric and wireless doorbells are primarily intended for home use, but can also be found in other areas. A long wireless range of wireless doorbells guarantees clear and smooth communication between the push button and the doorbell itself. A wide selection of design allows everyone to find doorbells for their taste, which will also embellish their interior space.

BEŽIČNA ZVONCA WIRELESS DOORBELLS



- Automatsko povezivanje**
LED indikator
 Kućište od sjajne plastike
 Auto-learning code
 LED indicator
 Glossy plastic housing
- 36 melodija**
 36 melodies
- 3 načina rada:**
 - zvonu + svjetlosna indikacija
 - samo zvonu
 - samo svjetlosna indikacija
 3 function options:
 - ring + LED flash
 - ring only
 - LED flash only

Slika / Photo	Šifra / Art. No.	Broj melodija / Number of melodies	Jačina zvona / Bell volume	Domet / Range	Tipkalo / Transmitter	Zvonca / Bell	Kom./kutija / Pcs/ctn	EAN
1	411-107	36	70 dB	300 m	DC 3V CR2032 baterija u pakiranju / battery included	2 x 1,5V DC AA baterije nisu u pakiranju / batteries not included	10	3858883839135
2	411-108	36	70 dB	300 m			10	3858890443691
3	411-109	36	70 dB	300 m			10	3858890443684



Šifra / Art. No.	Broj melodija / Number of melodies	Jačina zvona / Bell volume	Domet / Range	Tipkalo / Transmitter	Zvonce / Bell	Kom./kutija / Pcs/ctn	EAN
411-110	32	83 dB	100 m	DC 3V CR2032 baterija u pakiranju / battery included	2 x 1,5V DC AA baterije nisu u pakiranju / batteries not included	10	3856024402682



Šifra / Art. No.	Broj melodija / Number of melodies	Jačina zvona / Bell volume	Domet / Range	Tipkalo / Transmitter	Zvonce / Bell	Kom./kutija / Pcs/ctn	EAN
411-106	36	70 dB	300 m	DC 3V CR2032 baterija u pakiranju / battery included	2 x 1,5V DC AA baterije nisu u pakiranju / batteries not included	10	3858883838473

KINETIČKO ZVONCE
KINETIC DOORBELL



 **Bez baterija i žica**
No batteries, no wires required

Šifra / Art. No.	Broj melodija / Number of melodies	Jačina zvona / Bell volume	Domet / Range	Tipkalo / Transmitter	Zvonce / Bell	Kom./kutija / Pcs/ctn	EAN
411-111	36	80 dB	100 m	kinetičko / kinetic	100-240 V~	10	3856024403399

ZVONCE ZA DIN ŠINU
DIN RAIL BELL

Šifra / Art. No.	Jačina zvona / Bell volume	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
410-201	80 dB	220 - 240 V~ 50/60 Hz	12	3858890448603



ELEKTRIČNA ZVONCA
ELECTRIC DOORBELLS



Slika / Photo	Šifra / Art. No.	Broj melodija / Number of melodies	Jačina zvona / Bell volume	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
1	410-104	1	80 dB	230 V~	10	3856024402255
2	410-105	1	80 dB	230 V~	10	3856024402262
3	410-106	1	80 dB	230 V~	10	3856024402279

Portafoni

Commel portafoni omogućuju Vam glasovnu i vizualnu komunikaciju s posjetiteljima. Svi modeli dolaze s robusnim vanjskim jedinicama pojačane otpornosti na loše vremenske uvjete.

Door Phones

Commel video door phones allow you voice and visual communication with visitors. All models come with robust outdoor units with increased resistance to bad weather conditions.

Commel®



Sifra / Art. No.	Veličina zaslona / Screen size	Broj melodija / Number of melodies	Kom./kutija / Pcs/ctn	EAN
501-104	7"	16	4	3858890447262



7" zaslon u boji
16 melodija zvona
Handsfree komunikacija
7" color screen
16 ringtones
Handsfree communication

Mogućnost otključavanja 2 vrata
Napajanje: DC 12 V 1100 mA
Noćno snimanje: 1 m
Unlocking two doors
Power supply: DC 12 V 1100 mA
Night recording: 1 m

Dimenzije unutarnje jedinice: 215 x 152 x 18 mm
Dimenzije vanjske jedinice: 53 x 131 x 47 mm
Stupanj zaštite vanjske jedinice: IP44
Indoor unit dimensions: 215 x 152 x 18 mm
Outdoor unit dimensions: 53 x 131 x 47 mm
Outdoor unit protection degree: IP44



Šifra / Art. No.	Veličina zaslona / Screen size	Broj melodija / Number of melodies	Kom./kutija / Pcs/ctn	EAN
501-105	4,3"	16	8	3858890447279

- 4,3" zaslon u boji
16 melodija zvon
Handsfree komunikacija
4.3" color screen
16 ringtones
Handsfree communication

- Mogućnost otključavanja 2 vrata
Napajanje: DC 12 V 1100 mA
Noćno snimanje: 1 m
Unlocking two doors
Power supply: DC 12 V 1100 mA
Night recording: 1 m

- Dimenzije unutarnje jedinice: 136 x 143 x 18,5 mm
Dimenzije vanjske jedinice: 53 x 131 x 47 mm
Stupanj zaštite vanjske jedinice: IP44
Indoor unit dimensions: 136 x 143 x 18,5 mm
Outdoor unit dimensions: 53 x 131 x 47 mm
Outdoor unit protection degree: IP44



Šifra / Art. No.	Veličina zaslona / Screen size	Broj melodija / Number of melodies	Kom./kutija / Pcs/ctn	EAN
501-205	4,3"	16	4	3858890449952

- 4,3" zaslon u boji
16 melodija zvon
Handsfree komunikacija
4.3" color screen
16 ringtones
Handsfree communication

- Mogućnost otključavanja 2 vrata
Napajanje: DC 12 V 1100 mA
Noćno snimanje: 1 m
Unlocking two doors
Power supply: DC 12 V 1100 mA
Night recording: 1 m

- Dimenzije unutarnje jedinice: 136 x 143 x 18,5 mm
Dimenzije vanjske jedinice: 118 x 205 x 80 mm
Stupanj zaštite vanjske jedinice: IP44
Indoor unit dimensions: 136 x 143 x 18,5 mm
Outdoor unit dimensions: 118 x 205 x 80 mm
Outdoor unit protection degree: IP44



Šifra / Art. No.	Broj melodija / Number of melodies	Kom./kutija / Pcs/ctn	EAN
502-103	1	20	3858890449938



Šifra / Art. No.	Broj melodija / Number of melodies	Kom./kutija / Pcs/ctn	EAN
502-203	1	10	3858890449945



Ventilatori

Commel ventilatori namijenjeni su ugradnji u otvore od 100, 120 i 150 mm. U ponudi su i modeli s mogućnošću podešavanja odgode gašenja. Niska potrošnja električne energije i niska razina buke također su odlike Commel ventilatora.

Exhaust Fans

Energy-saving and low-noise exhaust fans from Commel are designed for installation into ventilation shafts of 100, 120 and 150 mm. There are models that also have delay timer.



Šifra / Art. No.	Snaga / Power	Max. protok zraka / Max air flow	Promjer otvora za ugradnju / Mounting diameter	Razina buke / Noise level	Brzina rotacije / Motor rotation	Stupanj zaštite / IP grade	Odgoda gašenja / timer Shut off delay / timer	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
420-101	12W	130 m³/h	100 mm	34 db	2400 rpm	IP X2	-	220-240 V~ 50 Hz	20	3858883835601
420-102	12W	130 m³/h	100 mm	34 db	2400 rpm	IP X2	x	220-240 V~ 50 Hz	20	3858883835618
420-111	16W	240 m³/h	120 mm	34 db	2200 rpm	IP X2	-	220-240 V~ 50 Hz	20	3858890446074
420-112	16W	240 m³/h	120 mm	34 db	2200 rpm	IP X2	x	220-240 V~ 50 Hz	20	3858890446067
420-121	18W	320 m³/h	150 mm	35 db	2000 rpm	IP X2	-	220-240 V~ 50 Hz	20	3858890446050
420-122	18W	320 m³/h	150 mm	35 db	2000 rpm	IP X2	x	220-240 V~ 50 Hz	20	3858890446043



Šifra / Art. No.	Snaga / Power	Max. protok zraka / Max air flow	Promjer otvora za ugradnju / Mounting diameter	Razina buke / Noise level	Brzina rotacije / Motor rotation	Stupanj zaštite / IP grade	Odgoda gašenja / timer Shut off delay / timer	Nazivni napon / Voltage	Kom./kutija / Pcs/ctn	EAN
420-103	12W	130 m³/h	100 mm	34 db	2400 rpm	IP X2	-	220-240 V~ 50 Hz	20	3858883835625
420-104	12W	130 m³/h	100 mm	34 db	2400 rpm	IP X2	x	220-240 V~ 50 Hz	20	3858883835632



Automatski osigurači i FID sklopke

Commel automatski osigurači i FID sklopke namijenjeni su ugradnji u kućanstva ali i za industrijsku upotrebu. Visoka proizvodna tehnologija i stroga kontrola kvalitete jamče pouzdanost ovih proizvoda u opasnim situacijama.

RCCB & Miniature Circuit Breaker

Commel circuit breakers and RCCBs are intended for installation in households but also for industrial use. High production technology and strict quality control guarantee the reliability of these products in dangerous situations.

FID SKLOPKA
RCCB



Šifra / Art. No.	Nazivna struja / Rated current	Polovi / Poles	Struja kratkog spojaja / Rated short circuit current	Osećljivost / Rated sensitivity	Kom./kutija / Pcs/ctn	EAN
470-140	40 A	2	6000A	0,3A	1	3856024401814
470-141	40 A	2	6000A	0,03A	1	3856024404280
470-125	25 A	2	6000A	0,03A	1	3856024401807



Šifra / Art. No.	Nazivna struja / Rated current	Polovi / Poles	Struja kratkog spojaja / Rated short circuit current	Osećljivost / Rated sensitivity	Kom./kutija / Pcs/ctn	EAN
470-263	63 A	4	6000A	0,03A	1	3856024404501
470-241	40 A	4	6000A	0,03A	1	3856024404297
470-225	25 A	4	6000A	0,03A	1	3856024404273

AUTOMATSKI OSIGURAČI
MINIATURE CIRCUIT BREAKER



Šifra / Art. No.	Nazivna struja / Rated current	Polovi / Poles	Karakteristika okidanja / Curve code	Struja kratkog spojaja / Rated short circuit current	Kom./kutija / Pcs/ctn	EAN
465-132	32 A	1	B	6000A	12	3856024401791
465-125	25 A	1	B	6000A	12	3856024401784
465-120	20 A	1	B	6000A	12	3856024401777
465-116	16 A	1	B	6000A	12	3856024401760
465-110	10 A	1	B	6000A	12	3856024401753
465-106	6 A	1	B	6000A	12	3856024401746
465-240	40 A	1	C	6000A	12	3856024404228
465-232	32 A	1	C	6000A	12	3856024404211
465-225	25 A	1	C	6000A	12	3856024404204
465-220	20 A	1	C	6000A	12	3856024404198
465-216	16 A	1	C	6000A	12	3856024404181
465-210	10 A	1	C	6000A	12	3856024404174



Šifra / Art. No.	Nazivna struja / Rated current	Polovi / Poles	Karakteristika okidanja / Curve code	Nazivna prekidna moć / Breaking capacity	Kom./kutija / Pcs/ctn	EAN
465-286	32 A	3	C	6000A	4	3856024404266
465-285	25 A	3	C	6000A	4	3856024404259
465-284	20 A	3	C	6000A	4	3856024404242
465-283	16 A	3	C	6000A	4	3856024404235

Montažni pribor


Proizvodi za pričvršćivanje ili organizaciju kabela neizostavni su kod većine električarskih radova. Commel nudi široki asortiman montažnog pribora namijenjenog hoby majstorima, ali i onog za profesionalnu upotrebu.



Mounting Accessories


Products for cable management are indispensable when doing electrical work. Commel offers a wide range of mounting accessories intended for hobby handymen, but also for professional users.

KABELSKE VEZICE CABLE TIES



Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-101	2,5 mm	100 mm	bijela / white	100	20	3858890440003
365-102	2,5 mm	100 mm	crna / black	100	20	3858890440027
365-103	2,5 mm	150 mm	bijela / white	100	20	3858890440041
365-104	2,5 mm	150 mm	crna / black	100	20	3858890440065
365-111	3,5 mm	150 mm	bijela / white	100	20	3858890440089
365-112	3,5 mm	150 mm	crna / black	100	20	3858890440102
365-113	3,5 mm	200 mm	bijela / white	100	20	3858890440126
365-114	3,5 mm	200 mm	crna / black	100	20	3858890440140
365-121	4,7 mm	300 mm	bijela / white	100	20	3858890440164
365-122	4,7 mm	300 mm	crna / black	100	20	3858890440188
365-123	4,7 mm	380 mm	bijela / white	50	20	3858890441147
365-124	4,7 mm	380 mm	crna / black	50	20	3858890441154
365-131	7,5 mm	250 mm	bijela / white	25	20	3858890441161
365-132	7,5 mm	250 mm	crna / black	25	20	3858890441178
365-133	7,5 mm	400 mm	bijela / white	25	20	3858890441185
365-134	7,5 mm	400 mm	crna / black	25	20	3858890441192

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-175	2,5 mm	150 mm	5 boja / 5 colors	100	20	3856024403252
365-176	3,6 mm	200 mm	5 boja / 5 colors	100	20	3856024403269
365-177	4,8 mm	300 mm	5 boja / 5 colors	100	20	3856024403276



Šifra / Art. No.	Kom./pak / Pcs/pkg	Specifikacija / Specification	Kom./kutija / Pcs/ctn	EAN
365-171	400	2,5 mm x 100 mm bijela / white x 200	20	3858890440201
		2,5 mm x 100 mm crna / black x 100		
		3,5 mm x 200 mm bijela / white x 50		
		3,5 mm x 200 mm crna / black x 50		



Šifra / Art. No.	Kom./pak / Pcs/pkg	Specifikacija / Specification	Kom./kutija / Pcs/ctn	EAN
365-172	300	2,5 mm x 100 mm crvena / red x 25	20	3858890447392
		2,5 mm x 100 mm žuta / yellow x 25		
		2,5 mm x 100 mm crna / black x 25		
		2,5 mm x 100 mm zelena / green x 25		
		2,5 mm x 100 mm bijela / white x 50		
		3,5 mm x 200 mm crvena / red x 50		
		3,5 mm x 200 mm plava / blue x 50		
		3,5 mm x 200 mm bijela / white x 50		



Šifra / Art. No.	Kom./pak / Pcs/pkg	Specifikacija / Specification	Kom./kutija / Pcs/ctn	EAN
365-173	170	2,5 mm x 100 mm x 100 3,5 x 200 mm x 40 4,5 mm x 200 mm x 30	12	3856024401739

KABELSKE VEZICE S RUPOM ZA PRIČVRŠĆIVANJE MOUNTABLE HEAD CABLE TIES

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-141	3,6 mm	100 mm	bijela / white	100	20	3856024403009
365-142	3,6 mm	100 mm	crna / black	100	20	3856024403016
365-143	3,6 mm	145 mm	bijela / white	100	20	3856024403023
365-144	3,6 mm	145 mm	crna / black	100	20	3856024403030
365-145	4,3 mm	220 mm	bijela / white	100	20	3856024403047
365-146	4,3 mm	220 mm	crna / black	100	20	3856024403054
365-147	7,6 mm	381 mm	bijela / white	25	20	3856024403061
365-148	7,6 mm	381 mm	crna / black	25	20	3856024403078



KABELSKE VEZICE ODVEZIVE RELEASABLE CABLE TIES



Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-001	7,5 mm	200 mm	bijela / white	25	20	3856024403085
365-002	7,5 mm	200 mm	crna / black	25	20	3856024403092
365-003	7,5 mm	250 mm	bijela / white	25	20	3856024403108
365-004	7,5 mm	250 mm	crna / black	25	20	3856024403115
365-005	7,5 mm	300 mm	bijela / white	25	20	3856024403122
365-006	7,5 mm	300 mm	crna / black	25	20	3856024403139
365-007	7,5 mm	370 mm	bijela / white	25	20	3856024403146
365-008	7,5 mm	370 mm	crna / black	25	20	3856024403153


KABELSKE VEZICE ZA VIŠEKRAATNU UPOTREBU / KNOT CABLE TIES

Šifra / Art. No.	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-151	120 mm	bijela / white	100	20	3858890445855
365-152	180 mm	bijela / white	100	20	3858890445862




KABELSKE VEZICE S DVOSTRUKOM OMČOM
DOUBLE LOOP CABLE TIES

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-051	4,8 mm	200 mm	bijela / white	50	20	3856024403191
365-052	4,8 mm	200 mm	crna / black	50	20	3856024403207



KABELSKE VEZICE, VATROTPORNE
FLAME RETARDANT CABLE TIES

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-161	3,6 mm	150 mm	bijela / white	100	20	3856024403160
365-162	3,6 mm	200 mm	bijela / white	100	20	3856024403177
365-163	4,8 mm	300 mm	bijela / white	100	20	3856024403184



 Samogasive, u skladu sa standardom UL94-V0
Fire-retardant, According to standard UL94-V0

METALNE KABELSKE VEZICE
STAINLESS STEEL CABLE TIES

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-181	4,6 mm	200 mm	25	20	3856024403214
365-182	4,6 mm	500 mm	25	20	3856024403221
365-183	7,9 mm	200 mm	25	20	3856024403238
365-184	7,9 mm	500 mm	25	20	3856024403245




KABELSKE VEZICE NA ČIČAK
VELCRO CABLE TIES

Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-191	12 mm	135 mm	crna / black	10	20	3856024403283
365-192	16 mm	210 mm	crna / black	10	20	3856024403290




SAMOLJEPLJIVI DRŽAČI VEZICA
SELF ADHESIVE TIE MOUNTS

Šifra / Art. No.	Dimenzije / Dimensions	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-331	20 x 20 mm	bijela / white	25	20	3858890447170
365-332	30 x 30 mm	bijela / white	25	20	3858890447187



KABELSKE OBUJMICE
CABLE CLIPS

Šifra / Art. No.	Promjer / Diameter	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-301	4-7 mm	bijela / white	100	1	3858890440225
365-302	7-10 mm	bijela / white	100	1	3858890440232
365-303	10-14 mm	bijela / white	50	1	3858890440249



Spojni pribor

Ne pristajemo na kompromise kad je u pitanju kvalitetan i siguran spoj električnih vodiča i kabela, bez obzira radi li se o klasičnim instalacijama u kućanstvu ili upotrebi u zahtjevnijim uvjetima.




Connection Accessories

We do not accept compromises when it comes to a quality and safe connection of electrical wires and cables, regardless of whether we are dealing with a household installation or the one in more demanding conditions.

Commel®


REDNE STEZALJKE TERMINAL BLOCKS



Šifra / Art. No.	Presjek vodiča / Wire cross section	Boja / Color	Kom./kutija / Pcs/ctn	EAN
365-401	2,5 mm²	bijela / white	20	3858890440256
365-402	4,0 mm²	bijela / white	20	3858890440270
365-403	6,0 mm²	bijela / white	20	3858890440294

Šifra / Art. No.	Presjek vodiča / Wire cross section	Boja / Color	Kom./kutija / Pcs/ctn	EAN
365-409	0,5 - 2,5 mm²	bijela / white	10	38588904404105

BRZE KABELKE SPOJNICE ZA PUNU ŽICU QUICK WIRE CONNECTORS FOR SOLID WIRE




Šifra / Art. No.	Polovi / Poles	Presjek vodiča / Wire cross section	Boja / Color	Kom./kutija / Pcs/ctn	EAN
365-464	2	0,75 - 2,5 mm²	žuta / yellow	20	3856024404044
365-467	2	0,75 - 2,5 mm²	žuta / yellow	50	3856024404051
365-465	4	0,75 - 2,5 mm²	narančasta / orange	20	3856024404068
365-468	4	0,75 - 2,5 mm²	narančasta / orange	50	3856024404075
365-466	6	0,75 - 2,5 mm²	ljubičasta / purple	10	3856024404082
365-469	6	0,75 - 2,5 mm²	ljubičasta / purple	50	3856024404099


BRZE KABELKE SPOJNICE
QUICK WIRE CONNECTORS




Šifra / Art. No.	Polovi / Poles	Presjek punog vodica / Solid wire cross section	Presjek fleksibilnog vodica / Stranded wire cross section	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-450	2	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	20	10	3858890449341
365-454	2	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	50	20	3856024404143
365-452	3	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	10	10	3858890442465
365-455	3	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	50	20	3856024404150
365-453	5	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	10	10	3858890442472
365-456	5	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	50	20	3856024404167




Šifra / Art. No.	Polovi / Poles	Presjek punog vodica / Solid wire cross section	Presjek fleksibilnog vodica / Stranded wire cross section	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-471	2	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	10	10	3856024404112



Šifra / Art. No.	Polovi / Poles	Presjek punog vodica / Solid wire cross section	Presjek fleksibilnog vodica / Stranded wire cross section	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-472	2-2	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	10	10	3856024403931
365-474	2-4	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	5	10	3856024403955
365-475	2-6	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	5	10	3856024403948




Šifra / Art. No.	Polovi / Poles	Presjek punog vodica / Solid wire cross section	Presjek fleksibilnog vodica / Stranded wire cross section	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-473	3-3	0,08 - 2,5 mm ²	0,08 - 4,0 mm ²	5	10	3856024403924
365-477	3-6	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	5	10	3856024404129
365-478	3-9	0,2 - 2,5 mm ²	0,2 - 4,0 mm ²	5	10	3856024404136



 **Mehanizam s brzom spojnicom za montažu bez odvijača**
Quick coupler mechanism for screwless installation

Šifra / Art. No.	Polovi / Poles	Presjek punog vodiča / Solid wire cross section	Presjek fleksibilnog vodiča / Stranded wire cross section	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Kom./kutija / Pcs/ctn	EAN
365-906	3	0,08 - 2,5 mm ²	0,08 - 4 mm ²	IP68	87 mm x 25 mm	10	3856024404013

KABELSKI KONEKTORI IP68
CABLE CONNECTOR IP68




Šifra / Art. No.	Polovi / Poles	Presjek vodiča / Wire cross section	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Kom./kutija / Pcs/ctn	EAN
365-901	3	0,5 - 2,5 mm	IP68	80 mm x 25 mm	10	3858890444377
365-903	5	0,5 - 4 mm	IP68	110 mm 32 mm	10	3856024402170
365-904	5	0,5 - 4 mm	IP68	110 mm x 100 mm x 32 mm	10	3856024402187

KABELSKI KONEKTOR IP68
CABLE CONNECTOR IP68




 Rastavljiv, klik mehanizam za montažu bez odvijača
Reconnectable, Click-on mechanism for screwless installation



Šifra / Art. No.	Polovi / Poles	Presjek vodiča / Wire cross section	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Kom./kutija / Pcs/ctn	EAN
365-902	3	0,5 - 2,5 mm	IP68	105 mm x 30 mm	10	3856024402163

VODOOTPORNI KONEKTORI IP68
WATERPROOF CONNECTORS IP68



Šifra / Art. No.	Polovi / Poles	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Kom./kutija / Pcs/ctn	EAN
365-921	2	IP68	135 x 70 x 40 mm	10	3856024403962
365-922	3	IP68	135 x 80 x 40 mm	10	3856024403979
365-923	4	IP68	135 x 80 x 40 mm	10	3856024403986
365-924	4	IP68	135 x 100 x 40 mm	10	3856024403993
365-925	6	IP68	135 x 100 x 40 mm	10	3856024404006

Izolacijski pribor

Proizvodi iz ove kategorije pružaju izvrsnu električnu izolaciju, ali i zaštitu električnih spojeva od prašine, vanjskih utjecaja i naprezanja. Izolir trake proizvodimo isključivo od samogasivih materijala.

Insulation Accessories


Products in this category provide excellent electrical insulation, but also protection of electrical connections from dust, external influences and stress. Our insulating tapes are made exclusively from self-extinguishing materials.



TERMO BUŽIRI
HEAT SHRINK TUBINGS



Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./kutija / Pcs/ctn	EAN
365-561	2,5 → 1,25 mm	1 m	crna / black	1	3858890445909
365-562	3,5 → 1,75 mm	1 m	crna / black	1	3858890445916
365-563	5,0 → 2,5 mm	1 m	crna / black	1	3858890445923
365-564	7,0 → 3,5 mm	1 m	crna / black	1	3858890445930
365-565	10,0 → 5,0 mm	1 m	crna / black	1	3858890445947
365-566	13,0 → 6,5 mm	1 m	crna / black	1	3858890445954



Šifra / Art. No.	Promjer / Diameter	Dužina / Length	Boja / Color	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-551	2,5 → 1,25 mm	1 m	crna / black	10	10	3858890441758
365-552	3,5 → 1,75 mm	1 m	crna / black	10	10	3858890441772
365-553	5,0 → 2,5 mm	1 m	crna / black	10	10	3858890441796
365-554	7,0 → 3,5 mm	1 m	crna / black	10	10	3858890441819
365-555	10,0 → 5,0 mm	1 m	crna / black	10	10	3858890441833
365-556	13,0 → 6,5 mm	1 m	crna / black	10	10	3858890441857

TERMO BUŽIRI
HEAT SHRINK TUBINGS

Boje / Colors




Šifra / Art. No.	Dužina / Length	Specifikacija / Specification	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-501	10 cm	1,5 mm x 30	100	20	3858890440355
		2,5 mm x 30			
		4,0 mm x 20			
		6,0 mm x 10			
		10,0 mm x 6			
		13,0 mm x 4			

IZOLIR TRAKE
INSULATING TAPES

- Samogasive
Fire retardant
- U skladu sa standardom EN 60454-2
According to standard EN 60454-2

Boje / Colors



Šifra / Art. No.	Boja / Color	Dužina / Length	Širina / Width	Debljina / Thickness	Kom./kutija / Pcs/ctn	EAN
365-601	crna / black	10 m	15 mm	0,13 mm	10	3858890440379
365-602	plava / blue	10 m	15 mm	0,13 mm	10	3858890440393
365-603	žuto-zelena / yellow-green	10 m	15 mm	0,13 mm	10	3858890440416
365-604	crvena / red	10 m	15 mm	0,13 mm	10	3858890440430
365-605	bijela / white	10 m	15 mm	0,13 mm	10	3858890441314
365-651	crna / black	10 m	19 mm	0,13 mm	10	3858890440454
365-652	plava / blue	10 m	19 mm	0,13 mm	10	3858890440478
365-653	žuto-zelena / yellow-green	10 m	19 mm	0,13 mm	10	3858890440492
365-654	crvena / red	10 m	19 mm	0,13 mm	10	3858890440515
365-655	bijela / white	10 m	19 mm	0,13 mm	10	3858890441338
365-656	zelena / green	10 m	19 mm	0,13 mm	10	3858890449204
365-657	žuta / yellow	10 m	19 mm	0,13 mm	10	3858890449211



Tuljci i stopice

Upotrebom tuljaka i stopica osiguravate čvrst i trajan električni spoj. Commel asortiman tuljaka i stopica sadrži proizvode različitih dimenzija i područja primjene, a isporučuju se u praktičnom blister pakiranju.

Wire Terminals

Wire terminals ensure a strong and lasting electrical connection. The Commel range of wire terminals contains products of various sizes and areas of application, and they come in a practical blister pack.



IZOLIRANI ZAVRŠNI TULJCI INSULATED CORD END TERMINALS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-801	0,75 mm ²	100	100	3858890444940
365-802	1,0 mm ²	100	100	3858890444957
365-803	1,5 mm ²	100	100	3858890444964
365-804	2,5 mm ²	100	100	3858890444971

TULJCI I STOPICE | WIRE TERMINALS

NEIZOLIRANI ZAVRŠNI TULJCI NON-INSULATED CORD END TERMINALS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-805	0,75 mm ²	100	100	3856024403320
365-806	1,0 mm ²	100	100	3856024403337
365-807	1,5 mm ²	100	100	3856024403344
365-808	2,5 mm ²	100	100	3856024403351

IZOLIRANI ZAVRŠNI TULJCI INSULATED CORD END TERMINALS



Šifra / Art. No.	Specifikacija / Specification	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-701	0,5 mm ² x 50	400	1	3858890440539
	0,75 mm ² x 100			
	1,0 mm ² x 100			
	1,5 mm ² x 100			
	2,5 mm ² x 50			


IZOLIRANE SPOJNE ČAHURE INSULATED CONNECTORS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-891	0,5 - 1,5 mm ²	20	100	3856024403306
365-892	1,5 - 2,5 mm ²	20	100	3856024403313

VILIČASTE STOPICE SPADE TERMINALS

Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-851	0,5 - 1,5 mm ² Ø 4,3 mm	25	100	3858890445077
365-852	1,5 - 2,5 mm ² Ø 5,3 mm	25	100	3858890445084



TULJCI I STOPICE | WIRE TERMINALS

OKRUGLE STOPICE
RING TERMINALS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-881	0,5 - 1,5 mm ² Ø 4,3 mm	25	100	3858890445152
365-882	0,5 - 1,5 mm ² Ø 5,3 mm	25	100	3858890445169
365-883	1,5 - 2,5 mm ² Ø 4,3 mm	25	100	3858890445176
365-884	1,5 - 2,5 mm ² Ø 5,3 mm	25	100	3858890445183
365-885	4,0 - 6,0 mm ² Ø 8,4 mm	10	100	3858890445190

KUTNI UTIKAČI + NATIKAČI ZA ŽICU
MALE + FEMALE WIRE DISCONNECTS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-841	0,5 - 1,5 mm ² / 0,8 x 6,35 mm	25 + 25	25	3858890445091
365-842	1,5 - 2,5 mm ² / 0,8 x 6,35 mm	25 + 25	25	3858890445107

UTIKAČI I NATIKAČI ZA ŽICU
WIRE DISCONNECTS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-811	0,5 - 1,5 mm ² / 0,8 x 2,8 mm	25	100	3858890445015
365-812	0,5 - 1,5 mm ² / 0,8 x 6,35 mm	25	100	3858890445053
365-813	1,5 - 2,5 mm ² / 0,8 x 4,75 mm	25	100	3858890445039

Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-821	0,5 - 1,5 mm ² / 0,8 x 2,8 mm	25	100	3858890445022
365-822	0,5 - 1,5 mm ² / 0,8 x 6,35 mm	25	100	3858890445060
365-823	1,5 - 2,5 mm ² / 0,8 x 4,75 mm	25	100	3858890445046

Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-831	0,5 - 1,5 mm ² / 0,8 x 4,75 mm	10 + 10	100	3858890444988
365-832	0,5 - 1,5 mm ² / 0,8 x 6,35 mm	10 + 10	100	3858890444995
365-833	1,5 - 2,5 mm ² / 0,8 x 4,75 mm	10 + 10	100	3858890445008

IZOLIRANI UTIKAČI I NATIKAČI ZA ŽICU
INSULATED BULLET TERMINALS



Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-861	izolirani utikač za žicu / insulated bullet terminal - male 0,5 - 1,5 mm ² / Ø 4 mm	25	100	3858890445114
365-862	izolirani utikač za žicu / insulated bullet terminal - male 1,5 - 2,5 mm ² / Ø 5 mm	25	100	3858890445121

Šifra / Art. No.	Dimenzije / Dimensions	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-871	izolirani natikač za žicu / insulated bullet terminal - female 0,5 - 1,5 mm ² / Ø 4 mm	25	25	3858890445138
365-872	izolirani natikač za žicu / insulated bullet terminal - female 1,5 - 2,5 mm ² / Ø 5 mm	25	25	3858890445145

SET STOPICA - 18 VRSTA
WIRE TERMINAL SET - 18 TYPES



Šifra / Art. No.	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-702	175	1	3858890445961

Električarski alati


Povećajte učinkovitost i uštedite vrijeme upotrebom praktičnih Commel električarskih alata za obradu vodiča i krimpanje stopica.

Hand Tools

When handling cables and wires, increase efficiency and save time by using practical Commel hand tools.



SET STOPICA S KLIJEŠTIMA
ELECTRICAL PLIERS AND TERMINALS SET



Šifra / Art. No.	Kom./pak / Pcs/pkg	Kom./kutija / Pcs/ctn	EAN
365-751	101	10	3858890442489

SAMOPODESIVA KLIJEŠTA ZA SKIDANJE IZOLACIJE
SELF-ADJUSTING WIRE STRIPPER



Šifra / Art. No.	Boja / Color	Kom./kutija / Pcs/ctn	EAN
370-101	crveno-crna / red-black	10	3856024403368



Šifra / Art. No.	Boja / Color	Kom./kutija / Pcs/ctn	EAN
370-102	crveno-crna / red-black	10	3856024403375



NAJLONSKA SAJLA ZA UVLAČENJE KABELA
NYLON FISH TAPE



Šifra / Art. No.	Boja / Color	Vrsta materijala / Type of Material	Dužina / Length	Promjer / Diameter	Kom./kutija / Pcs/ctn	EAN
370-301	plava / blue	najlon / nylon	5 m	3 mm	5	3856024403665
370-302	plava / blue	najlon / nylon	10 m	3 mm	5	3856024403672
370-303	plava / blue	najlon / nylon	20 m	3 mm	5	3856024403689



ČELIČNA SAJLA ZA UVLAČENJE KABELA
STEEL FISH TAPE



Šifra / Art. No.	Boja / Color	Vrsta materijala / Type of Material	Dužina / Length	Promjer / Diameter	Kom./kutija / Pcs/ctn	EAN
370-311	crna / black	čelik / steel	5 m	3 mm	5	3856024403696
370-312	crna / black	čelik / steel	10 m	3 mm	5	3856024403702
370-313	crna / black	čelik / steel	20 m	3 mm	5	3856024403719



Commel®

LED žarulje

Upotrebom LED žarulja ostvaruje se ušteda energije čak do 85% u odnosu na klasične žarulje sa žarnom niti. Životni vijek od 25.000 radnih sati omogućava dugogodišnje korištenje bez potrebe za učestalom izmjenom žarulja, pa je iz tog razloga LED rasvjeta ekološki najprihvatljiviji način osvjetljenja. Prednosti u odnosu na fluorescentne štedne žarulje su smanjena potrošnja električne energije, duži životni vijek i otpornost na učestalo uključivanje i isključivanje. LED žarulje ne sadrže otrovne tvari (živu, olovo, plinove,...), ne emitiraju štetna UV i IR zračenja, a omogućuju stabilno osvjetljenje bez treperenja i zujanja.

LED Bulbs

Compared to traditional incandescents, LED bulbs can achieve energy savings of up to 85%. The life span of 25,000 hours allows long-term use without the need for frequent bulb replacement, and for that reason LED lighting is the most environmentally acceptable way of illumination. The advantages of LED bulbs over CFL bulbs are lower power consumption, longer lifespan and resistance to damage caused by turning on and off repeatedly. LEDs do not contain toxic materials(mercury, lead, gases,...), they do not emit harmful UV and infrared radiation, and yet they provide stable illumination without flickering or buzzing.



E27/A60


Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-103	6 W	640 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446449
305-113	6 W	640 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446456
305-123	6 W	640 lm	6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890449709
305-101	8 W	806 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890444841
305-111	8 W	806 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446463
305-121	8 W	806 lm	6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890449716
305-102	9 W	1050 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890444858
305-112	9 W	1050 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446470
305-122	9 W	1050 lm	6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890447248
305-104	11 W	1350 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446494
305-114	11 W	1350 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446487
305-105	12 W	1500 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446500
305-115	12 W	1500 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890446517
305-125	12 W	1500 lm	6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890447620

LED ŽARULJE | LED BULBS



E27/A65


Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-106	16 W	1800 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890448528
305-116	16 W	1800 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890448542
305-126	16 W	1800 lm	6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890449723





E27/G45

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvratu boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-109	8 W	750 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890448566
305-119	8 W	750 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890448580



E27/R63



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvratu boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-131	8.5 W	780 lm	3000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890449518
305-132	8.5 W	780 lm	4000 K	RA >80	25.000 h	220-240 V~	E27	10	3858890449525

Žarulja s 3 temperature svjetla Vam omogućava promjenu ambijentalnog osvjetljenja i stvaranje različitog ugođaja jednostavnim pritiskom prekidača. Ako trebate „bijelo“ svjetlo za osvjetljavanje radne površine, „neutralno“ svjetlo kao imitaciju sunčeve dnevne svjetlosti ili „toplo“ osvjetljenje za opuštajuće trenutke, od sada Vam je sve dostupno sa samo jednom žaruljom. Kod prvog uključivanja žarulja će emitirati svjetlost od 3000 K(toplo bijelo). Svakim sljedećim uključivanjem unutar 5 sekundi od isključivanja temperatura svjetla će se promijeniti na 4000 K(neutralno bijelo), zatim na 6500 K(hladno bijelo).

The 3-color settings LED bulb allows you to change the ambient light and create a different atmosphere by simply pressing the switch. If you need a 'white' light to illuminate your working space, a 'neutral' light as imitation of daylight or a 'warm' light for relaxing moments, everything is possible now with just one bulb. When first turned on, the bulb emits a light of 3000 K(warm white). Every next turn on within 5 seconds after turning off, the color temperature will change to 4000 K(neutral white), and then to 6500 K(cool white).

E27/A60

ŽARULJA S 3 TEMPERATURE SVJETLA 3-STEP CCT CHANGE BULB



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvratu boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-162	11 W	1050 lm	3000 K / 4000 K / 6500 K	RA >80	25.000 h	220-240 V~	E27	10	3858890447224

GU10



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvratu boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-304	3 W	250 lm	3000 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890446562
305-305	5 W	400 lm	3000 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890446579
305-315	5 W	400 lm	4000 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890446586
305-325	5 W	400 lm	6500 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890449754
305-302	7 W	540 lm	3000 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890444889
305-312	7 W	540 lm	4000 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890446593
305-322	7 W	540 lm	6500 K	RA >80	25.000 h	220-240 V~	GU10	10	3858890449761



E14/C37

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-201	6 W	500 lm	3000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890444865
305-211	6 W	500 lm	4000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890446524
305-221	6 W	500 lm	6500 K	RA >80	25.000 h	220-240 V~	E14	10	3858890447255
305-203	8 W	750 lm	3000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890446531
305-213	8 W	750 lm	4000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890449730
305-223	8 W	750 lm	6500 K	RA >80	25.000 h	220-240 V~	E14	10	3858890449747



E14/G45

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-202	6 W	500 lm	3000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890444872
305-212	6 W	500 lm	4000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890446548
305-204	8 W	750 lm	3000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890446555



E14/R50

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-231	5 W	450 lm	3000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890449532
305-232	5 W	450 lm	4000 K	RA >80	25.000 h	220-240 V~	E14	10	3858890449549

G9

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-401	3.5 W	315 lm	3000 K	RA >80	25.000 h	220-240 V~	G9	20	3858890446760



GU5.3/MR16

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-411	6 W	560 lm	3000 K	RA >80	25.000 h	12 V	GU5.3	10	3858890449556
305-412	6 W	560 lm	4000 K	RA >80	25.000 h	12 V	GU5.3	10	3858890449563



G4

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Nazivni napon / Input voltage	Baza / Base	Kom./kutija / Pcs/ctn	EAN
305-405	1.8 W	180 lm	3000 K	RA >80	25.000 h	12 V	G4	20	3858890446777





Commel®

LED trake

LED trake imaju široku primjenu u osvjetljavanju unutarnjih i vanjskih prostora. Koriste se kao primarna rasvjeta u osvjetljavanju kuhinjskih radnih površina, unutrašnjosti ormara ili gazišta stepenica, ali i kao diskretno ambijentalno osvjetljenje montažom u spuštene stropove, iza namještaja, ispod šankova...

LED Strip Lights

LED strips have wide application in indoor and outdoor lighting, from kitchen under cabinet lighting to illumination of stair treads, interiors of closets, but also as indirect ambient light when mounted in dropped ceilings, behind furniture, under a bar...

LED TRAKE | LED STRIP LIGHTS



Sifra / Art. No.	Temperatura svjetla / Color Temperature	Dužina / Length	Broj LED chipova / Number of LED chips	Stupanj zaštite / IP grade	Životni vijek / Lifespan	Napon / Voltage	Daljinski upravljač / Remote control	Kom./kutija / Pcs/ctn	EAN
405-203	RGB	3 m	180	IP65	15.000 h	12 V	+	20	3858890440638
405-205	RGB	5 m	300	IP65	15.000 h	12 V	+	20	3858890440652
405-103	6500 K	3 m	180	IP65	15.000 h	12 V	-	20	3858890440577
405-105	6500 K	5 m	300	IP65	15.000 h	12 V	-	20	3858890440591
405-113	3000 K	3 m	180	IP65	15.000 h	12 V	-	20	3858890441598
405-115	3000 K	5 m	300	IP65	15.000 h	12 V	-	20	3858890441581
405-153	3000 K	3 m	90	IP20	15.000 h	12 V	-	20	3858890441567



Sifra / Art. No.	Temperatura svjetla / Color Temperature	Dužina / Length	Snaga / Power	Broj LED chipova / Number of LED chips	Stupanj zaštite / IP grade	Životni vijek / Lifespan	Napon / Voltage	Daljinski upravljač / Remote control	Kom./kutija / Pcs/ctn	EAN
405-405	RGB	5 m	24 W	300	IP44	20.000 h	220-240 V~	+	6	3856024402002




Zidne i stropne LED svjetiljke

Prednosti svjetiljki iz ove kategorije su kompaktan dizajn, mogućnost serijskog spajanja, jednostavna i brza montaža te ugrađeni prekidač radi lakšeg rukovanja.

LED Under Cabinet Light Fixtures

The advantages of these light fixtures are compact design, possibility of serial connecting, easy and quick mounting and a built-in switch for easier operation.



- Mogućnost serijskog spajanja**
Possibility of serial connection with connector
- PC kućište, sa sklopkom**
PC housing, On/off switch
- Priključni kabel s utikačem je uključen u pakiranje**
Connection cable with plug included in the package

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
406-205	4 W	400 lm	480 lm	6500 K	RA >80	30.000 h	282 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448610
406-215	4 W	400 lm	480 lm	4000 K	RA >80	30.000 h	282 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448658
406-206	7 W	700 lm	840 lm	6500 K	RA >80	30.000 h	582 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448627
406-216	7 W	700 lm	840 lm	4000 K	RA >80	30.000 h	582 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448665
406-207	10 W	1000 lm	1200 lm	6500 K	RA >80	30.000 h	882 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448634
406-217	10 W	1000 lm	1200 lm	4000 K	RA >80	30.000 h	882 x 21 x 31mm	IP20	220 - 240 V~ 50 Hz	30	3858890448672
406-208	14 W	1400 lm	1680 lm	6500 K	RA >80	30.000 h	1182 x 21 x 31 mm	IP20	220 - 240 V~ 50 Hz	30	3858890448641
406-218	14 W	1400 lm	1680 lm	4000 K	RA >80	30.000 h	1182 x 21 x 31 mm	IP20	220 - 240 V~ 50 Hz	30	3858890448689



- Kabel za serijsko spajanje LED svjetiljkije**
Cable connector for LED under cabinet light fixtures

Šifra / Art. No.	Dužina / Length	Boja / Color	Kom./kutija / Pcs/ctn	EAN
406-902	20 cm	bijela / white	1	3858890448696



Proizvodi su opremljeni senzorom pokreta kratkog dometa koji ima mogućnost upravljanja radom svjetiljke na jedan od ova dva načina:

- Uključivanje i isključivanje svjetiljke jednostavnim pokretom ruke.
- Kod ugradnje u ormar, uključivanje svjetiljke prilikom otvaranja vrata i isključivanje prilikom zatvaranja vrata.



Način rada se jednostavno podešava na prekidaču koji se nalazi s bočne strane svjetiljke.

The products are equipped with a short-range motion detector which can operate the light fixture in one of these two modes:

- Turns ON and OFF the light fixture when you wave your hand.
- When installed in a cabinet, turns ON the light fixture when door is opened, and turns it OFF when door is closed.


The modes are easily set on the switch located on the side of the lamp.

-  **Detektor pokreta - uključivanje / isključivanje pokretom ruke**
Motion detector - turning ON / OFF by hand movement



-  **Mogućnost ugradnje u ormar - automatsko uključivanje prilikom otvaranja vrata**
Suitable for installation inside cabinet - turning ON when door is opening

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
406-501	3 W	210 lm	280 lm	4000 K	RA >80	30.000 h	325 x 25 x 14 mm	IP20	100 - 240 V~ 50/60 Hz	20	3858890449969
406-502	5.5 W	400 lm	550 lm	4000 K	RA >80	30.000 h	525 x 25 x 14 mm	IP20	100 - 240 V~ 50/60 Hz	20	3858890449976
406-503	9.5 W	680 lm	920 lm	4000 K	RA >80	30.000 h	940 x 25 x 14 mm	IP20	100 - 240 V~ 50/60 Hz	20	3858890449983



Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
406-261	9 W	900 lm	1000 lm	4000 K	RA >80	30.000 h	300 x 25 x 75 mm	IP20	220 - 240 V~ 50/60 Hz	20	3856024402521
406-262	18 W	1800 lm	2200 lm	4000 K	RA >80	30.000 h	600 x 25 x 75 mm	IP20	220 - 240 V~ 50/60 Hz	20	3856024402538
406-263	27 W	2500 lm	3400 lm	4000 K	RA >80	30.000 h	900 x 25 x 75 mm	IP20	220 - 240 V~ 50/60 Hz	20	3856024402545
406-264	36 W	3400 lm	4500 lm	4000 K	RA >80	30.000 h	1200 x 25 x 75 mm	IP20	220 - 240 V~ 50/60 Hz	20	3856024402569



Zidne i stropne svjetiljke

Čvrste i robusne zidne i stropne svjetiljke namijenjene su osvjetljavanju podrumskih, radioničkih, balkonskih i ostalih prostora na kojima je potreba dodatna fizička zaštita stakla. Veći stupanj IP zaštite omogućava njihovu primjenu i u vlažnim prostorima.

Bulkhead Light Fixtures

Solid and robust bulkhead light fixtures are intended for illuminating basements, workshops, balconies and other areas where glass cover needs to be protected. A higher degree of IP protection enables their application also in damp spaces.



Slika / Photo	Šifra / Art. No.	Boja / Color	Grlo / Lamp holder	Max snaga / Max power	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/cn	EAN
1	331-201	siva / gray	E27	60 W	170 x 125 x 115 mm	IP54	230 V~ 50 Hz	12	3856024402286
2	331-205	siva / gray	E27	100 W	195 x 135 x 115 mm	IP44	230 V~ 50 Hz	12	3856024402514
3	331-111	crna / black	E27	60 W	170 x 125 x 115 mm	IP54	230 V~ 50 Hz	12	3856024403726
3	331-112	bijela / white	E27	60 W	170 x 125 x 115 mm	IP54	230 V~ 50 Hz	12	3856024403733
3	331-113	siva / gray	E27	60 W	170 x 125 x 115 mm	IP54	230 V~ 50 Hz	12	3856024403740



LED plafonjere

Iako izgledom podsjećaju na klasične plafonjere iz prošlosti, Commel LED plafonjere nemaju ugrađenu klasičnu žarulju već LED modul koji omogućava znatnu uštedu energije i vrlo dugi vijek trajanja. Za zahtjevnije uvjete rada, vlažne prostore tu su i LED plafonjere sa većom IP zaštitom.

LED Ceiling Lamps

Although they look like classic ceiling lamps from the past, Commel LED ceiling lamps do not have built-in light bulbs but LED module that can achieve considerable energy savings and has a long lifespan. For more demanding operating conditions like humid spaces, there are also LED ceiling lamps with higher IP degree of protection.



Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
407-125	12 W	840 lm	1200 lm	4000 K	RA >80	25.000 h	260 mm	IP20	220-240 V~ 50/60 Hz	10	3856024403429
407-126	18 W	1260 lm	1850 lm	4000 K	RA >80	25.000 h	330 mm	IP20	220-240 V~ 50/60 Hz	10	3856024403436
407-127	24 W	1680 lm	2500 lm	4000 K	RA >80	25.000 h	380 mm	IP20	220-240 V~ 50/60 Hz	10	3856024403443
407-128	30 W	2240 lm	3150 lm	4000 K	RA >80	25.000 h	380 mm	IP20	220-240 V~ 50/60 Hz	10	3856024403450



Mikrovalni detektor pokreta
Art.No. 407-201, 407-202, 407-203
Microwave motion detector
Art.No. 407-201, 407-202, 407-203



Vodootporna kutija za ožičenje se nalazi s vanjske strane kućišta pa nema potrebe za otvaranjem svjetiljke prilikom montaže


The waterproof wiring box is located on the outer side of housing so there is no need for disassembling the lamp housing when mounting

Stezaljke za prihvat kabela bez vijaka omogućavaju jednostavnu i brzu montažu

Screwless cable clamps allow easy and quick mounting

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Detektor pokreta / Motion detector	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
407-101	15 W	1500 lm	2000 lm	-	4000 K	RA >80	30.000 h	220 mm	IP54	220-240 V~ 50/60 Hz	10	3858890444636
407-102	18 W	1850 lm	2550 lm	-	4000 K	RA >80	30.000 h	280 mm	IP54	220-240 V~ 50/60 Hz	10	3858890444643
407-103	24 W	2500 lm	3200 lm	-	4000 K	RA >80	30.000 h	330 mm	IP54	220-240 V~ 50/60 Hz	10	3858890444650
407-201	15 W	1500 lm	2000 lm	4 - 8 m	4000 K	RA >80	30.000 h	220 mm	IP54	220-240 V~ 50/60 Hz	10	38588904448979
407-202	18 W	1850 lm	2550 lm	4 - 8 m	4000 K	RA >80	30.000 h	280 mm	IP54	220-240 V~ 50/60 Hz	10	38588904448986
407-203	24 W	2500 lm	3200 lm	4 - 8 m	4000 K	RA >80	30.000 h	330 mm	IP54	220-240 V~ 50/60 Hz	10	38588904448993

3U1 LED PLAFONJERE
3 IN 1 LED CEILING LAMPS



Sa sklopkom za odabir temperature svjetla

With CCT switch for color temperature adjustment

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
407-105	18 W	1800 lm	1880 lm	3000/4000/6500 K	RA >80	25.000 h	220 mm	IP54	165-265 V~ 50/60 Hz	20	3856024402651
407-106	24 W	2400 lm	2565 lm	3000/4000/6500 K	RA >80	25.000 h	280 mm	IP54	165-265 V~ 50/60 Hz	10	3856024402668
407-107	30 W	3000 lm	3255 lm	3000/4000/6500 K	RA >80	25.000 h	330 mm	IP54	165-265 V~ 50/60 Hz	10	3856024402675

LED paneli

Elegantan način osvjetljavanja Vaših poslovnih i stambenih prostora moguć je s novom generacijom učinkovitih LED panela. Zamjenom klasičnih rasvjetnih tijela ne dobiva se samo ljepši izgled već i značajna ušteda energije, čak do 85%.

LED Panels

With a new generation of highly efficient LED panels, it is possible to illuminate your business and residential premises in a more elegant way. By replacing the traditional lighting fixtures you will get not only a more attractive design but also significant energy savings of up to 85%.




Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Promjer otvora za montažu / Cutout diameter	Nazivni napon / Input voltage	Kom./kutija / Pcs/cdn	EAN
337-351	3 W	240 lm	260 lm	3000 K	RA >80	25.000 h	90 mm	75 mm	220-240 V~ 50/60 Hz	10	3856024402088
337-352	3 W	240 lm	260 lm	4000 K	RA >80	25.000 h	90 mm	75 mm	220-240 V~ 50/60 Hz	10	3856024402095
337-362	6 W	480 lm	520 lm	4000 K	RA >80	25.000 h	120 mm	108 mm	220-240 V~ 50/60 Hz	10	3856024402101
337-372	12 W	960 lm	1200 lm	4000 K	RA >80	25.000 h	170 mm	158 mm	220-240 V~ 50/60 Hz	10	3856024402118
337-382	18 W	1440 lm	1850 lm	4000 K	RA >80	25.000 h	225 mm	206 mm	220-240 V~ 50/60 Hz	10	3856024402125



 **Integrirani driver**
Integrated driver


 **Brza montaža LED panela na nosač - "klik" sistem, bez upotrebe odvijača**
Quick and easy mounting of LED panel - "click" system, without the use of a screwdriver

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-366	6 W	480 lm	520 lm	4000 K	RA >80	25.000 h	120 mm	220-240 V~ 50/60 Hz	10	3856024402088
337-376	12 W	960 lm	1200 lm	4000 K	RA >80	25.000 h	170 mm	220-240 V~ 50/60 Hz	10	3856024402118
337-386	18 W	1440 lm	1850 lm	4000 K	RA >80	25.000 h	225 mm	220-240 V~ 50/60 Hz	10	3856024402125


COLOUR
TEMPERATURE
SWITCH

 **Integrirani driver**
Integrated driver

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Promjer otvora za montažu / Cutout diameter	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-304	6 W	400 lm	525 lm	2700/4000/6500 K	RA >80	25.000 h	115 mm	105 mm	220-240 V~ 50/60 Hz	50	3856024402323
337-314	12 W	900 lm	1190 lm	2700/4000/6500 K	RA >80	25.000 h	170 mm	155 mm	220-240 V~ 50/60 Hz	40	3856024402330
337-324	18 W	1500 lm	1880 lm	2700/4000/6500 K	RA >80	25.000 h	220 mm	205 mm	220-240 V~ 50/60 Hz	20	3856024402347
337-334	24 W	1950 lm	2565 lm	2700/4000/6500 K	RA >80	25.000 h	240 mm	225 mm	220-240 V~ 50/60 Hz	20	3856024402422



 **Integrirani driver**
Integrated driver

COLOUR
TEMPERATURE
SWITCH

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije svjetiljke / Lamp dimensions	Dimenzije otvora za montažu / Cutout dimensions	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-404	6 W	400 lm	525 lm	2700/4000/6500 K	RA >80	25.000 h	120 x 120 mm	105 x 105 mm	220-240 V~ 50/60 Hz	50	3856024402439
337-414	12 W	900 lm	1190 lm	2700/4000/6500 K	RA >80	25.000 h	170 x 170 mm	155 x 155 mm	220-240 V~ 50/60 Hz	40	3856024402446
337-424	18 W	1500 lm	1880 lm	2700/4000/6500 K	RA >80	25.000 h	220 x 220 mm	205 x 205 mm	220-240 V~ 50/60 Hz	20	3856024402354
337-434	24 W	1950 lm	2565 lm	2700/4000/6500 K	RA >80	25.000 h	220 x 220 mm	205 x 205 mm	220-240 V~ 50/60 Hz	20	3856024402453



- Integrirani driver
Integrated driver
- Brza montaža LED panela na nosač - “klik” sistem, bez upotrebe odvijača
Quick and easy mounting of LED panel - “click” system, without the use of a screwdriver

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Faktor snage / Power factor	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-308	6 W	400 lm	525 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	122 mm	220-240 V ~ 50/60 Hz	50	3856024402361
337-318	12 W	900 lm	1190 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	177 mm	220-240 V ~ 50/60 Hz	40	3856024402378
337-328	18 W	1500 lm	1880 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	226 mm	220-240 V ~ 50/60 Hz	20	3856024402385
337-338	24 W	1950 lm	2565 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	245 mm	220-240 V ~ 50/60 Hz	20	3856024402392




- Integrirani driver
Integrated driver
- Brza montaža LED panela na nosač - “klik” sistem, bez upotrebe odvijača
Quick and easy mounting of LED panel - “click” system, without the use of a screwdriver

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Faktor snage / Power factor	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije svjetiljke / Lamp dimensions	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-408	6 W	400 lm	525 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	122x122 mm	220-240 V ~ 50/60 Hz	50	3856024402460
337-418	12 W	900 lm	1190 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	172x172 mm	220-240 V ~ 50/60 Hz	40	3856024402477
337-428	18 W	1500 lm	1880 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	227x227 mm	220-240 V ~ 50/60 Hz	20	3856024402408
337-438	24 W	1950 lm	2565 lm	2700/4000/6500 K	>0.9	RA >80	25.000 h	227x227 mm	220-240 V ~ 50/60 Hz	20	3856024402415



Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije svjetiljke / Lamp dimensions	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-601	40 W	4000 lm	5000 lm	4000 K	RA >80	30.000 h	595 x 595 x 30 mm	220-240 V~ 50 Hz	5	3856024402088

Šifra / Art. No.	Snaga / Power	Svjetlosni tok Luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Dimenzije svjetiljke / Lamp dimensions	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
337-505	40 W	3200 lm	4700 lm	4000 K	RA >80	30.000 h	595 x 595 x 10 mm	180-265 V~ 50/60 Hz	5	3858890447583
337-503	45 W	4500 lm	5400 lm	4000 K	RA >80	30.000 h	595 x 595 x 10 mm	220-240 V~ 50/60 Hz	5	3858890449358
337-504	45 W	4500 lm	5400 lm	6500 K	RA >80	30.000 h	595 x 595 x 10 mm	220-240 V~ 50/60 Hz	5	3858890449365
337-515	40 W	3200 lm	4700 lm	4000 K	RA >80	30.000 h	1195 x 295 x 10 mm	220-240 V~ 50/60 Hz	5	3858890449372



Slika / Photo	Šifra / Art. No.	Opis / Description	Dimenzije svjetiljke / Lamp dimensions	Kom./kutija / Pcs/ctn	EAN
1	337-901	set za nadgradnu montažu LED panela 595x595 mm / surface mount kit for LED panel 595x595 mm	600 x 600 x 50 mm	20	3858890443417
1	337-903	set za nadgradnu montažu LED panela 1195x295 mm / surface mount kit for LED panel 1195x295 mm	1200 x 300 x 50 mm	20	3858890444094
2	337-902	nosači s oprugom za montažu LED panela (pakiranje 4 komada) / spring clips for LED panel (4 pcs)	-	1	3858890443905

LED ugradbene svjetiljke

Zahvaljujući jednostavnom i elegantnom dizajnu, LED ugradbene svjetiljke će se savršeno uklopiti u svaki interijer. Usmjerenim svjetlom idealno ćete naglasiti detalje u Vašem domu ili poslovnom prostoru.

LED Downlights

Thanks to their simple and elegant design, LED downlights will fit perfectly into any interior. With a focused beam of light, you will be able to accentuate the details in your home or office.



LED UGRADBENE SVJETILJKE | LED DOWNLIGHTS

Pakiranje sadrži set od 3 svjetiljke

3-pack set of downlights

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Promjer svjetiljke / Lamp diameter	Promjer otvora za montažu / Cutout diameter	Nazivni napon / Input voltage	Kom./pak / Pcs./pkg	Kom./kutija / Pcs./ctn	EAN
336-121	5 W	280 lm	390 lm	2700 K	RA >80	120°	20.000 h	86 mm	70-75 mm	220-240 V~ 50/60 Hz	3	20	3858890447484
336-122	5 W	280 lm	390 lm	4000 K	RA >80	120°	20.000 h	86 mm	70-75 mm	220-240 V~ 50/60 Hz	3	20	3858890447491

Commel®

145

LED cijevi

Commel LED cijevi namijenjene su za ugradnju u sve vrste raster i vodotijesnih svjetiljki. Kućište od nano polikarbonata smanjuje mogućnost mehaničkog oštećenja prilikom montaže ili transporta uz bolje raspršivanje svjetlosti.

LED Tubes

Commel LED tubes are designed for installation in all types of grille and waterproof light fixtures. The nano PC housing reduces the possibility of mechanical damage when mounting or transporting and provides higher dispersion of light.



-  **Napajanje s jedne strane**
Single end input
-  **Montaža u svjetiljke bez prigušnice i startera**
Mounting in lamps without ballast or starter

-  **Nano PC - LED cijevi s difuzorom od nano polikarbonata imaju mnogo prednosti u odnosu na LED cijevi sa staklenim ili plastičnim difuzorom. Nano polikarbonat omogućuje odličnu provodljivost i bolje raspršivanje svjetlosti te otpornost na mehanička oštećenja**

Nano PC - LED tubes with nano polycarbonate diffuser have many advantages over LED tubes with glass or plastic diffuser. Nano polycarbonate provides excellent transmittance and higher dispersion of light, and also high resistance to mechanical damage

Šifra / Art. No.	Snaga / Power	Tip / Type	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Faktor snage / Power factor	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Napajanje / Input voltage	Kom./kutija / Pcs/ctn	EAN
305-603	9 W	T8 60 cm	900 lm	4000 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890442328
305-613	9 W	T8 60 cm	900 lm	6500 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890442335
305-601	18 W	T8 120 cm	1850 lm	4000 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890441697
305-611	18 W	T8 120 cm	1850 lm	6500 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890442342
305-606	23 W	T8 150 cm	2400 lm	4000 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890442359
305-616	23 W	T8 150 cm	2400 lm	6500 K	>0.9	RA >80	25.000 h	185-240 V~ 50 Hz	25	3858890442366

LED vodotijesne svjetiljke

Kućište od ABS plastike i difuzor od polikarbonata uz ugrađene visokokvalitetne Commel LED cijevi i integrirane LED sklopove omogućuju LED vodotijesnim svjetilkama vrhunske karakteristike uz minimalne troškove električne energije. Zbog vrlo visokog stupnja IP zaštite pogodne su za ugradnju u vrlo vlažne prostore.


LED Waterproof Light Fixtures

ABS housing, polycarbonate diffuser, built-in high quality integrated LED or Commel LED tubes along with low power consumption, provide the highest quality performance of Commel LED waterproof light fixtures. Due to a very high IP degree of protection they are suitable for installation in very damp spaces.

Commel®



LED VODOTIJESNE SVJETILJKE | LED WATERPROOF LIGHT FIXTURES



IP65 brzi konektor za spajanja kabela
IP65 quick cable connector

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Materijal kućišta / Housing material	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
344-673	18 W	1800 lm	2100 lm	4000 K	RA >80	30.000 h	PC	690x55x35 mm	IP65	220-240 V~ 50/60 Hz	24	3856024403832
344-671	36 W	3600 lm	4100 lm	4000 K	RA >80	30.000 h	PC	1285x55x35 mm	IP65	220-240 V~ 50/60 Hz	24	3856024403825
344-676	45 W	4500 lm	5200 lm	4000 K	RA >80	30.000 h	PC	1585x55x35 mm	IP65	220-240 V~ 50/60 Hz	24	3856024403849



Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminaire luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Materijal kućišta / Housing material	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
344-653	18 W	1800 lm	2000 lm	4000 K	RA >80	25.000 h	ABS+PC	600x55x35 mm	IP65	220-240 V~ 50/60 Hz	20	3856024401449
344-651	36 W	3600 lm	4000 lm	4000 K	RA >80	25.000 h	ABS+PC	1200x55x35 mm	IP65	220-240 V~ 50/60 Hz	20	3856024401463



Šifra / Art. No.	Tip / Type	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Materijal kućišta / Housing material	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
344-607	2 x 10 W	2 x 1000 lm	4000 K	RA >80	25.000 h	ABS+PC	660x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402071
344-617	2 x 10 W	2 x 1000 lm	6500 K	RA >80	25.000 h	ABS+PC	660x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402040
344-608	2 x 18 W	2 x 1900 lm	4000 K	RA >80	25.000 h	ABS+PC	1260x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402026
344-618	2 x 18 W	2 x 1900 lm	6500 K	RA >80	25.000 h	ABS+PC	1260x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402057
344-609	2 x 24 W	2 x 2550 lm	4000 K	RA >80	25.000 h	ABS+PC	1560x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402033
344-619	2 x 24 W	2 x 2550 lm	6500 K	RA >80	25.000 h	ABS+PC	1560x80x96 mm	IP65	220-240 V~ 50/60 Hz	8	3856024402064

Šifra / Art. No.	Snaga / Power	Svjetlosni tok svjetiljke / Luminare luminous flux	Svjetlosni tok izvora svjetlosti / Light source luminous flux	Temperatura svjetla / Color temperature	Indeks uzvrata boje / CRI	Životni vijek / Lifespan	Materijal kućišta / Housing material	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
344-663	21 W	2520 lm	3000 lm	4000 K	RA >80	30.000 h	PC	590x72x61 mm	IP65	220-240 V~ 50/60 Hz	15	3856024402606
344-661	40 W	4800 lm	5600 lm	4000 K	RA >80	30.000 h	PC	1180x72x61 mm	IP65	220-240 V~ 50/60 Hz	12	3856024402590
344-666	55 W	6600 lm	7400 lm	4000 K	RA >80	30.000 h	PC	1480x72x61 mm	IP65	220-240 V~ 50/60 Hz	9	3856024402613



5 godina jamstva
5 year warranty

Panik svjetiljke

Commel LED panik svjetiljke vrhunske su kvalitete i trajnosti. Autonomija rada u panik modu od 3 sata omogućuje siguran izlaz iz zatvorenih prostora u slučaju nestanka električne energije. Vrlo visoki stupanj IP zaštite omogućuje montažu u vlažne prostore.

Emergency Light Fixtures

Commel LED emergency light fixtures are of very high quality and are very durable. Emergency operation time of 3 hours allows safe exit from enclosed areas in the event of power failure. A very high degree of IP protection enables installation in damp spaces.

Commel®



LED PANIK SVJETILJKE
LED EMERGENCY LIGHT FIXTURES





Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Autonomija rada / Working autonomy	Temperatura svjetla / Color temperature	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
346-201	4 W	160 lm	3 h	6000 K	352 x 110 x 57 mm	IP65	220-240 V~ 50 Hz	12	3858890440829



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Autonomija rada / Working autonomy	Temperatura svjetla / Color temperature	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
346-202	3.3 W	150 lm	3 h	6000 K	254 x 93 x 56 mm	IP65	220-240 V~ 50 Hz	12	3856024401869

zidna instalacija
wall instalation



stropna instalacija
ceilling instalation



Šifra / Art. No.	Snaga / Power	Autonomija rada / Working autonomy	Baterija / Battery	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
346-203	2.2 W	3 h	Ni-Cd 3.6 V 800 mAh	345 x 215 x 40 mm	IP20	220-240 V~ 50 Hz	6	3856024403856

Solarni LED reflektori

Commel solarne reflektore odlikuje visoka razina osvjetljenja i duga autonomija rada. Ne zahtijevaju dodatni izvor napajanja pa pokrivaju neograničena područja primjene. Zahvaljujući modernom dizajnu savršeno će se uklopiti u svaki vanjski ambijent.



Commel®

Solar LED Floodlights

Commel solar floodlights provide a high level of illumination and long working autonomy. They do not require an additional power source, so they cover unlimited areas of application. Thanks to the modern design, they will fit perfectly into any outdoor environment.

SOLARNI LED REFLEKTORI | SOLAR LED FLOODLIGHTS





2 godine jamstva
2 year warranty



2 načina montaže
2 mounting ways



2 načina rada
2 working modes



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Baterija / Battery	Temperatura svjetla / Color temperature	Dimenzije / Dimensions	Stupanj zaštite / IP grade	Kom./kutija / Pcs/ctn	EAN
309-101	8 W	800 lm	18650 3.7V 2000mAh	4000 K	290 x 178 x 140 mm	IP54	12	3856024403580
309-102	11 W	1500 lm	18650 3.7V 4000mAh	4000 K	290 x 178 x 140 mm	IP54	12	3856024403597

LED reflektori

Svi možete pronaći nešto za svoje potrebe u asortimanu Commel LED reflektora. Bilo da tražite dekorativni, radni ili profesionalni, a uz to i pristupačan LED reflektor, sve je tu. Izbor je na Vama!

LED Floodlights

Commel offers a wide range of LED floodlights. Whether you are looking for a decorative floodlight, work, professional, but also an affordable one, it is all there. The choice is yours!



Visoka kvaliteta, elegantan dizajn i pristupačna cijena glavne su odlike ove linije.

High quality, elegant design and affordable price are the main features of this line.

DETEKTOR POKRETA - podešavanje vremena, osjetljivosti i razine ambijentalnog osvjetljenja

MOTION DETECTOR - Adjustment of time, sensitivity and ambient light level disassembly

Šifra / Art. No.	Boja / Color	Snaga / Power	Detektori pokreta / Motion detector	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
306-119	bijela / white	10 W	-	800 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	60	3856024402729
306-219	crna / black	10 W	-	800 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	60	3856024402736
306-129	bijela / white	20 W	-	1600 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	40	3856024402743
306-229	crna / black	20 W	-	1600 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	40	3856024402750
306-139	bijela / white	30 W	-	2550 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	30	3856024402767
306-239	crna / black	30 W	-	2550 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	30	3856024402774
306-159	bijela / white	50 W	-	4250 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	20	3856024402781
306-259	crna / black	50 W	-	4250 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	20	3856024402798
306-199	bijela / white	100 W	-	8500 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	10	3856024402804
306-299	crna / black	100 W	-	8500 lm	4000 K	120°	30.000 h	IP65	220-240 V~ 50/60 Hz	10	3856024402811
307-119	bijela / white	10 W	120°	800 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	60	3856024402828
307-219	crna / black	10 W	120°	800 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	60	3856024402835
307-129	bijela / white	20 W	120°	1600 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	40	3856024402842
307-229	crna / black	20 W	120°	1600 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	40	3856024402859
307-139	bijela / white	30 W	120°	2550 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	20	3856024402866
307-239	crna / black	30 W	120°	2550 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	20	3856024402873
307-159	bijela / white	50 W	120°	4250 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	20	3856024402880
307-259	crna / black	50 W	120°	4250 lm	4000 K	120°	30.000 h	IP44	220-240 V~ 50/60 Hz	20	3856024402897



2 godine jamstva
2 year warranty


Vodootporni konektor
Waterproof connector



2 godine jamstva
2 year warranty

Detektor pokreta s mogućnošću
podešavanja načina rada
Motion detector with adjustable settings

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Detektor pokreta / Motion detector	Temperatura svjetla / Color temperature	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Nazivni napon / Input voltage	Kom. /kutija / Pcs/ctn	EAN
306-213	10 W	1 x 1000 lm	-	4000 K	120°	25.000 h	IP65	103 x 60 x 74 mm	220-240 V~ 50 Hz	60	3856024402934
306-223	20 W	1 x 2100 lm	-	4000 K	120°	25.000 h	IP65	122 x 60 x 97 mm	220-240 V~ 50 Hz	50	3856024402941
306-233	30 W	1 x 3200 lm	-	4000 K	120°	25.000 h	IP65	148 x 60 x 112 mm	220-240 V~ 50 Hz	30	3856024402958
306-253	50 W	1 x 5400 lm	-	4000 K	120°	25.000 h	IP65	196 x 62 x 146 mm	220-240 V~ 50 Hz	20	3856024402965
307-223	20 W	1 x 2100 lm	120°	4000 K	120°	25.000 h	IP44	124 x 73 x 180 mm	220-240 V~ 50 Hz	40	3856024402972
307-233	30 W	1 x 3200 lm	120°	4000 K	120°	25.000 h	IP44	148 x 73 x 200 mm	220-240 V~ 50 Hz	20	3856024402989
307-253	50 W	1 x 5400 lm	120°	4000 K	120°	25.000 h	IP44	198 x 73 x 234 mm	220-240 V~ 50 Hz	10	3856024402996



5 godina jamstva
5 year warranty


50 000 h životni vijek
50 000 h lifespan



Premium
line.



Šifra / Art. No.	Boja / Color	Snaga / Power	Svjetlosni tok / Luminous flux	Dimenzije / Dimensions	Temperatura svjetla / Color temperature	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Stupanj zaštite / IP grade	Nazivni napon / Input voltage	Kom. /kutija / Pcs/ctn	EAN
306-271	crna / black	70 W	9450 lm	255 x 198 x 36 mm	4000 K	120°	50.000 h	IP65	220-240 V~ 50/60 Hz	10	3856024403504
306-272	crna / black	100 W	13500 lm	315 x 233 x 38 mm	4000 K	120°	50.000 h	IP65	220-240 V~ 50/60 Hz	5	3856024403511
306-273	crna / black	150 W	20250 lm	375 x 280 x 38 mm	4000 K	120°	50.000 h	IP65	220-240 V~ 50/60 Hz	5	3856024403528
306-274	crna / black	200 W	27000 lm	410 x 298 x 40 mm	4000 K	120°	50.000 h	IP65	220-240 V~ 50/60 Hz	4	3856024403535



H05RN-F kabel s IP44 šuko utikačem
H05RN-F cable with IP44 Schuko plug

Šifra / Art. No.	Tip / Type	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Stupanj zaštite / IP grade	Kabel / Cable	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
308-213	10 W	1 x 1000 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	10	3856024403764
308-233	30 W	1 x 3200 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	10	3856024403771
308-253	50 W	1 x 5400 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	8	3856024403801



H05RN-F kabel s IP44 šuko utikačem
H05RN-F cable with IP44 Schuko plug

Teleskopski stalak s mogućnošću podešavanja visine
Height adjustable tripod telescopic stand

Šifra / Art. No.	Tip / Type	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Kut snopa svjetlosti / Beam angle	Životni vijek / Lifespan	Stupanj zaštite / IP grade	Kabel / Cable	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
308-433	1 x 30 W	1 x 3200 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	2	3856024403788
308-533	2 x 30 W	2 x 3200 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	2	3856024403795
308-553	2 x 50 W	2 x 5400 lm	6500 K	120°	25.000 h	IP44	H05RN-F 3G1 / 2,5 m	220-240 V~ 50 / 60 Hz	2	3856024403818

Akumulatorski LED reflektori

Akumulatorski LED reflektori su namijenjeni korištenju u uvjetima gdje nemamo pristup izvoru električne energije. Ugrađene litijske baterije i kvalitetni LED sklopovi pružaju visoku razinu osvjetljenja i dugu autonomiju rada. Zahvaljujući praktičnom sklopivom dizajnu vrlo lako ćete ih pospremiti u ladicu, kutiju s alatom, ruksak za kampiranje ili automobil.

Rechargeable LED Floodlights

Rechargeable LED floodlights are intended to be used when there is no access to electricity. Built-in rechargeable Li-ion batteries and high quality LED provide a high level of illumination and long working autonomy. Thanks to practical self-folding design, you can easily keep them in a drawer, a toolbox, a camping backpack or a car.



USB punjač, do 2 sata neprekidnog rada
USB charger, up to 2 h of continuous operation

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Autonomija / Autonomy	Stupanj zaštite / IP	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
308-311	10 W	600 lm	>2 h	IP54	3.7 V, 2000 mAh, Li-Ion	10	3856024402712



Praktičan sklopivi dizajn
Practical self-folding design

2 razine osvjetljenja
2 brightness settings

Do 4 sata neprekidnog rada
Up to 4 h of continuous operation

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Temperatura svjetla / Color temperature	Kut. snopa svjetlosti / Beam angle	Stupanj zaštite / IP	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
308-310	10 W	600 lm	6500 K	110°	IP44	3.7 V 2600 mAh	10	3858890447347

Radne i prenosive svjetiljke

Commel radne i prenosive svjetiljke su jednostavno i praktično rješenje kada Vam nedostaje svjetlosti u radionici, garaži ili na kampiranju. Ovisno o njihovoj primjeni i Vašim specifičnim potrebama, možete odabrati između onih koje rade na napajanje iz električne mreže, prenosivih punjivih ili pak onih koje se pune sunčevom svjetlosti.

Inspection and Portable Lamps

Commel inspection lamps are a simple and practical solution when you need more light in a workshop, garage or at a campsite. Depending on their application and your specific needs, you can choose between those operating on power supply, power rechargeable ones or even solar rechargeable ones.



- USB punjač, Senzorski prekidač**
 USB charger, Sensor switch
- Uključivanje i isključivanje jednostavnim pokretom ruku**
 Turning the lamp ON or OFF by simple hand wave



- USB punjač, Senzorski prekidač**
 USB charger, Sensor switch
- Uključivanje i isključivanje jednostavnim pokretom ruku**
 Turning the lamp ON or OFF by simple hand wave



- USB punjač, Senzorski prekidač**
 USB charger, Sensor switch
- Uključivanje i isključivanje jednostavnim pokretom ruku**
 Turning the lamp ON or OFF by simple hand wave



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Kabel / Cable	Autonomija / Autonomy	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
401-212	5 W	350 lm	IPx5	USB	4 h	Li-ion 3.7 V, 800 mAh	10	3856024402705



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Kabel / Cable	Autonomija / Autonomy	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
401-210	5 W	300 lm	IPx5	USB	3 h	Li-ion 3.7 V, 800 mAh	10	3856024402507



Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Kabel / Cable	Autonomija / Autonomy	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
401-211	11 W	500 lm	IPx5	USB	2,5 h	Li-ion 3.7 V, 1500 mAh	10	3856024402699



- COB LED 3 W + SMD LED 3 W, USB punjač**
COB LED 3 W + SMD LED 3 W, USB charger

- LED indikator stanja baterije, Snažan magnetski držač**
Battery status LED indicator, Powerful magnetic holder

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Nazivni napon / Input voltage	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
401-020	3 W + COB LED 3 W	250 lm	IP44	27 x 19 x 162 mm	5 V 1 A	Lithium 3.7 V 1200 mAh	50	3858890449921



- USB punjač**
LED indikator stanja baterije
USB charger
Battery status LED indicator

- Snažan magnetski držač**
Mogućnost rotacije 360°
Powerful magnetic holder
360° rotation capability

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Dimenzije / Dimensions	Nazivni napon / Input voltage	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
401-015	COB LED 10 W	580 lm	IP44	34 x 378 mm	5 V 1 A	Lithium 3.7 V 2000 mAh	50	3858890449914

- Metalna zaštitna košara**
Metal protective grille

Šifra / Art. No.	Snaga / Power	Tip gria / Bulb socket	Stupanj zaštite / IP grade	Kabel / Cable	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
340-010	max 60 W	E27	IP20	H05RN-F 2x0,75 / 5m	220-240 V~ 50 Hz	8	3858890442564



- PVC zaštitna košara**
PVC protective grille

Šifra / Art. No.	Snaga / Power	Tip gria / Bulb socket	Stupanj zaštite / IP grade	Kabel / Cable	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
0885	max 60 W	E27	IP20	H05RN-F 2x0,75 / 5m	220-240 V~ 50 Hz	10	385988558588



- Električna mreža za hvatanje komaraca**
Vodootporna – IPX6, praktična kuka za vješanje
Mosquito killer grid, Waterproof – IPX6, practical hanger

- 3 razine osvjetljenja: 20% ; 50% ; 100%**
Do 20 h neprekidnog rada
3 light modes: 20%, 50% and 100%
Up to 20 h of continuous operation


Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Stupanj zaštite / IP grade	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
401-711	1 W	180 lm	IPX6	Li-Polymer 3.7 V 2000 mAh	20	3858890448382



- 3 u 1: prenosiva ručna svjetiljka + kamp svjetiljka + SOS svjetiljka**
2 razine osvjetljenja + SOS signalno svjetlo
3 in 1: flashlight + camping lamp + SOS emergency lamp
2 light modes + SOS flashing

- 2 načina punjenja: solarni panel ili USB punjač**
Dodatni izvor napajanja za elektroničke uređaje – power bank
Do 10 h neprekidnog rada, praktična sklopiva ručica
2 charging ways: solar panel or USB charging
Power bank – additional power source for electronic devices
Up to 10 h of continuous operation, practical foldable handle

Šifra / Art. No.	Snaga / Power	Svjetlosni tok / Luminous flux	Baterija / Battery	Kom./kutija / Pcs/ctn	EAN
401-712	1 W	65 lm	Lithium 3.7 V 800 mAh	20	3858890448399



Noćna svjetla

Jednostavno pretvorite bilo koju utičnicu u izvor svjetla. Commel noćna svjetla pružaju diskretno osvjetljenje u noćnim satima, a najčešće se upotrebljavaju za osvjetljavanje dječjih soba, hodnika ili stubišta. Zahvaljujući ugrađenom fotosenzoru, svjetlo će se automatski uključivati i isključivati, ovisno o razini ambijentalnog osvjetljenja.

Night Lights

Simply turn any socket into a light source. Commel night lights provide discreet lighting at nighttime hours. They are most commonly used to illuminate children's rooms, hallways or staircases. Thanks to a built-in photosensor, a nightlight will automatically switch on and off, depending on ambient brightness.



NOĆNO SVJETLO S PROJEKTOROM
NIGHT LIGHT WITH PROJECTOR



Šifra / Art. No.	Snaga / Power	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
390-203	0.7 W	220-240 V ~ 50 Hz	10	3856024403382



Ugrađeni fotosenzor automatski uključuje i isključuje svjetlo, ovisno o razini ambijentalnog osvjetljenja.
A built-in photosensor automatically switches on and off a nightlight, depending on ambient brightness.

Šifra / Art. No.	Snaga / Power	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
390-201	0.4 W	220-240 V ~ 50 Hz	20	3858890440676

Detektori pokreta i luksomati

Detektori pokreta i luksomati predviđeni su za automatizaciju upravljanja rasvjetnim tijelima i električnim uređajima. Kutovi detekcije, razni načini ugradnje i dometa kao i različita tehnologija detekcije pokreta omogućuju da svatko pronađe svoj idealan detektor pokreta ili luksomat.



Motion Detectors and Photocell Sensors

Motion detectors and photocell sensors are designed for automation of light fixtures and electrical appliances. They come in different varieties of detection angles, ways of installation, detection ranges as well as with different motion detection technologies, so you can find a perfect motion detector or photocell sensor for yourself.

INFRACRVENI DETEKTORI POKRETA
INFRARED MOTION DETECTORS



Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
311-151	bijela / white	360°	12 m	1200 W	IP20	220-240 V~ 50 Hz	50	3858883835250



Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
311-101	bijela / white	360°	6 m	1200 W	IP20	220-240 V~ 50 Hz	50	3858883835236
311-102	crna / black	360°	6 m	1200 W	IP20	220-240 V~ 50 Hz	50	3858883835243



Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
311-105	bijela / white	360°	6 m	2000 W	IP20	220-240 V~ 50 Hz	50	3858890447217



Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
311-201	bijela / white	360°	6 m	1200 W	IP20	220-240 V~ 50 Hz	50	3858883835274



Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
310-101	bijela / white	180°	12 m	1200 W	IP44	220-240 V~ 50 Hz	50	3858883835212
310-102	crna / white	180°	12 m	1200 W	IP44	220-240 V~ 50 Hz	50	3858883835229
310-103	srebrna / silver	180°	12 m	1200 W	IP44	220-240 V~ 50 Hz	50	3858890440874



Ugradnja u kutiju Ø 60 mm
Mounting in Ø 60 mm wall backbox

Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
312-101	bijela / white	160°	9 m	500 W	IP20	220-240 V~ 50 Hz	100	3858890440881

SENZORSKI PREKIDAČ SENSOR SWITCH

Senzorski prekidač se koristi za uključivanje i isključivanje svjetla jednostavnim pokretom ruke. Opremljen je senzorom kratkog dometa koji kod svake detekcije pokreta naizmjenično uključuje i isključuje priključeno rasvjetno tijelo.

The sensor switch is used to turn the light on and off with a simple hand movement. Equipped with a short-range sensor that switches the connected lighting fixture on and off at each motion detection.



Šifra / Art. No.	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Nazivna struja / Rated current	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
311-205	5-6 cm	500 W	5 A	IP20	220-240 V~ 50 Hz	100	3858890447613

MIKROVALNI DETEKTOR POKRETA MICROWAVE MOTION DETECTOR



Mikrovalni (radarski) detektor pokreta je opremljen senzorima visoke osjetljivosti i predstavlja najkvalitetnije rješenje za automatizirano uključivanje priključenih uređaja ili rasvjetnih tijela. Za detekciju pokreta nije potrebna optička vidljivost jer mikrovalni signal prolazi kroz tanke stijene zidova ili staklo, pa je zbog toga pogodan za montažu unutar kućišta svjetiljke, u spuštene stropove ili razvodne kutije.

Microwave motion detector is equipped with high sensitivity sensors and it is the best solution for automated switching on/off of connected devices or lighting fixtures. Motion detection does not require optical visibility because microwave signal passes through thin walls or glass and is therefore suitable for mounting inside a lamp housing, dropped ceilings or junction boxes.

Šifra / Art. No.	Boja / Color	Kut detekcije / Detection angle	Dometa detekcije / Detection range	Nazivno opterećenje / Rated load	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
313-101	bijela / white	360°	8 m	500 W	IP20	220-240 V~ 50 Hz	100	3858890440898



LUKSOMATI PHOTOCELL SENSORS

Šifra / Art. No.	Nazivna struja / Rated current	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
314-101	6 A	IP44	220-240 V~ 50 Hz	100	3858890443431

Šifra / Art. No.	Nazivna struja / Rated current	Suparni zaštite / IP grade	Nazivni napon / Input voltage	Kom./kutija / Pcs/ctn	EAN
314-201	10 A	IP44	220-240 V~ 50 Hz	100	3858890443448



Grla i pribor za rasvjetu

Ova grupa proizvoda obuhvaća PBT i keramička grla različitih namjena, kao i spojni pribor za montažu rasvjetnih tijela.

Bulb Sockets and Lighting Accessories


This product group includes PBT and ceramic bulb sockets for various purposes, as well as fittings for lighting fixtures installation.



PBT GRLA
PBT BULB SOCKETS



Šifra / Art. No.	Boja / Color	Baza / Base	Maks. temperatura / Max. temperature	Materijal kućišta / Housing material	Dimenzije / Dimensions	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-105	bijela / white	E14	210 °C	PBT	26 x 56 mm	250 V ~	2 A	50	3858890449846
016-115	crna / black	E14	210 °C	PBT	26 x 56 mm	250 V ~	2 A	50	3858890449853
016-101	bijela / white	E27	210 °C	PBT	38.5 x 59 mm	250 V ~	4 A	50	3858890449808
016-111	crna / black	E27	210 °C	PBT	38.5 x 59 mm	250 V ~	4 A	50	3858890449815



Šifra / Art. No.	Boja / Color	Baza / Base	Maks. temperatura / Max. temperature	Materijal kućišta / Housing material	Dimenzije / Dimensions	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-106	bijela / white	E14	210 °C	PBT	43 x 55 mm	250 V ~	2 A	50	3858890449860
016-116	crna / black	E14	210 °C	PBT	43 x 55 mm	250 V ~	2 A	50	3858890449877
016-102	bijela / white	E27	210 °C	PBT	57 x 59 mm	250 V ~	4 A	50	3858890449822
016-112	crna / black	E27	210 °C	PBT	57 x 59 mm	250 V ~	4 A	50	3858890449839

GRLO E27 S KABELOM
E27 BULB SOCKET WITH CABLE



Šifra / Art. No.	Boja / Color	Materijal kućišta / Housing material	Maks. temperatura / Max. temperature	Dužina kabela / Cable length	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-701	bijela / white	PBT	210 °C	17 cm	250 V ~	2 A	25	3858890449495
016-702	crna / black	PBT	210 °C	17 cm	250 V ~	2 A	25	3858890449501

GRLO GU10
GU10 BULB SOCKET



Šifra / Art. No.	Boja / Color	Materijal kućišta / Housing material	Dužina vodiča / Wire length	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-401	bijela / white	keramika /ceramic	9 cm	250 V ~	2 A	50	3856024402248

KERAMIČKA GRLA
CERAMIC BULB SOCKETS

Šifra / Art. No.	Baza / Base	Materijal kućišta / Housing material	Maks. temperatura / Max. temperature	Dimenzije / Dimensions	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-135	E40	Keramika / Ceramic	400 °C	54 x 69 mm	750 V ~	16 A	100	3858890449907



Šifra / Art. No.	Baza / Base	Materijal kućišta / Housing material	Maks. temperatura / Max. temperature	Dimenzije / Dimensions	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-131	E27	Keramika / Ceramic	400 °C	40 x 46 mm	250 V ~	4 A	400	3858890449884



Šifra / Art. No.	Baza / Base	Materijal kućišta / Housing material	Maks. temperatura / Max. temperature	Dimenzije / Dimensions	Nazivni napon / Voltage	Maks. opterećenje / Max. load	Kom./kutija / Pcs/ctn	EAN
016-132	E27	Keramika / Ceramic	400 °C	40 x 46 mm	250 V ~	4 A	400	3858890449891







Commel - Zagreb d.o.o.
Samoborska cesta 143 · 10090 Zagreb · Croatia
T: +385 1 3436 000
F: +385 1 3436 010
www.commel.hr
info@commel.hr

